THE WIND

Filed under Remonumentation Act 345 of 1990

JAN 2 2 2001

LAND CORNER RECORDATION CERTIFICATE

RECTION

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in Lenawee	Located In:	Corner Code #	BS 51 }		LII	BER 2	PAGE 21	
(County)						STATE LENA	OF MICHIGA WEE COUNTY FILED	V
1. Public Land Survey	T <u>-6-S</u> R <u>-1-E</u> TR	1-4	• •		5 DEC 2000 9:47:11 AM			
	T R T R						A J. DANIEL ER OF DEEDS	
2. Property Controlling STR								
3. Miscellaneous STR								
				1 [<u>"</u>
	Recorded Plat			2 6 3 —	5	4 3	2 .1	-
				4 7 5 —	8	9 10	11 - 12	!
I, <u>Clenn E. Richard</u> , in a field survey on <u>October 31, 2000</u> , do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a				6 18 7	17	16 15	14 13	_
				8 19 9 —	20	21 22	23 24	-
Court of Law; established expressed below:	e with the rules of the Michigan Board ed, re-established, monumented, re	-monumented, recover	od found as	10 30 11	29	28 27	26 25	<u>-</u>
	4 corners, all in the same town a	nd range, may be re		12 31 13	32	33 34	35 36	
on this certifica								
A. Description of original monument and accessories and/or subsequent restoration: G.L.O. 1815 Thomas Evans set 1/4 Sec. post. Hickory 20 S 4 E 22. B. Oak 22 N 4 E 19								
W 1/4 corner, NE corner, W 1/2, SW 1/4 and the NW corner, E 1/2, SE 1/4 of Section 10 at 1/2 the distance measured between the NE corner, W 1/2, SW 1/4 and the NW corner, E 1/2, SE 1/4. 1888 James Blair did survey and shows the corner but not type of monumentation 1920 J.L. Richard's records show "SW corner of house N 14 E 79 links "(52.14') 1922 John L. Richard the corner is the point of beginning for Plat of Geneva Beach, Liber 5, Page 33 1941 Walter Frazier the corner is the point of beginning for Supervisors Plat of Addition to Geneva Beach L7, P45. 1954 BLM did Dependent resurvey of Section 11. Hugh Crawford found wood stake in black top road over re-rod and granite stone. Replaced with conc. monument with brass cap 1958 I found the BLM monument 1970 Kenneth Suydam found the BLM monument 1971± The corner was dug out during sewer construction 1991 Werner Sommer set a iron pipe in the pavement by retracing the Supervisor's Plat of Addition to Geneva Beach. SW cor of house N 12° E 52.0 NE cor of Sterling Market N 45° W 174.88 SW cor of Sterling Market N 75° W 174.44 NE cor of bldg S 13° E 107.80 NW cor of bldg S 20° W 81.79 1995 I found iron pipe in pavement								
B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:								
Oct. 31, 2000 Kevin Pickford P.S. 46682 Found 3/4" iron pipe under base course of new asphalt pavement. Replaced it with 5/8" X 3' re-rod with Lenawee County Re-mon cap stamped P.S. 13040 and set monument box.								
C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:								
	d with Lenawee County Re-mor he best available evidence of th			ument bo	x and i	S SHAFF	T Market	
dbl hd nail & r dbl hd nail & r NE corner of S SW corner of Plat monumer	house N 15° E 51.88 (siding) re-mon tag in E.P. S 70° E 59.92 re-mon tag in TP S 50° W 50.62 Sterling Store N 45° W 174.88 Sterling Store N 75° W 174.44 nt East 207.90		0.4.			PI N	ENN IL. CHARD D. 13040	1
Ratified by Peer Group in accordance with P.A. 345 Co. Rep. Mount Child Date November 28, 2000 months of the Signed by Menn L. Richard Date Nov. 29, 2000 Glenn E. Richard								
		100.29, 2000						
Surveyor's Michigan Lic	cense No. 13040		FORM APPI	ROVED BY MICH	IIGAN STATE	BOARD OF LAND	SURVEYORS, JAN.	28, 1971