

JAN 22 2001

Filed under Remonumentation Act 345 of 1990

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Lenawee
(County)

Located In:

Corner Code #



LIBER 1

PAGE 401

STATE OF MICHIGAN
LENAWEE COUNTY
FILED

28 JUN 2000 8:42:54 AM

VICTORIA J. DANIELS
REGISTER OF DEEDS

1. Public Land Survey

T 6-S R 3-E

A-1 ✓

T 5-S R 2-E

M-13

T 5-S R 3-E

A-13

T 6-S R 2-E

M-1

2. Property Controlling

S T R

in Section

S T R

3. Miscellaneous

S T R

Property in Sec

S T R

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, Glenn E. Richard in a field survey on May 16, 2000

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O. 1815-1816 Benjamin Hough D.S. established the Township corner B Oak S 54 W 12 1/2 Beech 14 West 3 Late 1800's In J. Blair's records described the corner as "Stone & bricks in north road ditch= SE corner Section 36" 1953 Werner Sommer while employed by Walter Frazier found bricks in north road ditch, set iron pipe 2' deep & placed bricks & stone around it and another iron pipe at the surface 1958 Kenneth Suydam found iron pipe 1973 Werner Sommer found iron pipe and recorded it in Liber 2, Page 453 for A-1 6-3 1975 Werner Sommer found iron pipe and recorded it in Liber 3, Page 155 for M-1 6-2 1978 Kenneth Suydam found iron pipe and recorded it in Liber 4, Page 139 for A-13 5-3 1983 Werner Sommer set a 1" X 10" iron pipe over large stone by extending line west 226.49' (record) from buggy axle (called for in Blairs records) and recorded it in Liber 5, Page 89 for M-13 5-2 1993 Werner Sommer found 1" iron pipe 1995 Michael Bartolo found 1" iron pipe along northerly edge of gravel road which checked the remaining two witnesses and recorded it in Liber 5, Page 267 for M-1 6-2

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

May 1, 2000 Found 1" iron pipe as recorded by M. Bartolo in Liber 5, Page 267
May 16, 2000 Found 1" X 10" iron pipe on top of stone 14" X 10". Split it to get out of hole. Several other 4" to 6" diameter stones around it. While digging to enlarge the hole I found a 3/4" X 15" split seam iron pipe 0.36 south beside the stone over another iron pipe 2' deep 0.45 south surrounded by bricks. Set 30" Harrison monument @ location of the found 1" X 10" I.P. over stone

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

30" Harrison Monument stamped P.S. 13040 and is accepted as the best available evidence of the position of the original corner.
2' North of N. edge of gravel road & 6" below level of road
Fd dbl hd nail & disc in E.P. S 70° W 78.99
S. edge of Carsonite post North 0.53
Center of top on tele. pedestal S 35° E 67.15
Stop sign post S 20° E 64.90
Face of Road sign post S 35° W 43.03
Fd. nail & disc in E. P. S 20° W 94.24
1 1/4" iron pipe over buggy axle S 76° E 226.52

atified by Peer Group in accordance with P.A. 345 Co. Rep. Glenn E. Richard Date May 9, 2000

igned by Glenn E. Richard Date June 5, 2000

Glenn E. Richard

urveyor's Michigan License No. 13040

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971

REVISED MAY 14, 1975

REVISED JAN., 1983

ADAPTED FOR WORD PROCESSING MARCH, 1993