

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Luce (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____ T _____ R _____ T _____ R _____	_____ _____ _____
2. Property Controlling in Section	S 32 T 47N R 11W S 32 T 47N R 11W S _____ T _____ R _____	5 9 _____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____ S _____ T _____ R _____	_____ _____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims		

I, Stephan J. Szyszkoski, in a field survey on 5 10/18/2010 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(5-Sec. 32) North 1/16 corner, Section 32. Not established in the original survey.

(9-Sec. 32) East 1/16 corner, Section 32. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(5-Sec. 32) Established the corner midway and on a straight line between Quarter corner 1317.50'
north and the intersection of 1/4 lines of Section 32 1317.50' south.

(9-Sec. 32) Established the corner midway and on a straight line between Quarter corner 1287.52' east
and the intersection of 1/4 lines of Section 32 1287.52' west.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(5) Set 1"IDx36" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
8" twin Sugar S46W 5.65' mrkd "N1/16 BT"
5" Sugar N46W 16.35' do
12" Maple N43E 18.25' do
16" Maple S61E 26.5' do
Bearings are magnetic.

(9) Set 1"IDx36" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
8" Cherry N34E 12.05' mrkd "E1/16 BT"
9" W.Pine N89W 28.2' do
6" W.Pine S45W 37.05' do
5" W.Spruce S12W 26.5' do
Bearings are magnetic.

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 11/16/2010

For the Michigan Department of Natural Resources and Environment, Forest Management Division

