

# SURVEY & REMONUMENTATION

FEB 26 2001

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in

### SECTION

LIVINGSTON

(County)

Located in:

Corner Code #

1. Public Land Survey

T 1N R 3E

H-07

T R

T R

T R

T R

2. Property Controlling  
in Section

S

T R

S

T R

3. Miscellaneous  
Property in Sec.

S

T R

S

T R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

2000 NOV 15 A 9:30

NANCY HAVILAND  
REGISTER OF DEEDS  
LIVINGSTON COUNTY, MI.  
48843

LSC #1375m

9 Register of Deeds Stamp & File Number

I, DARRELL D. HUGHES, in a field survey on November 7, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO: 1825, Sylvester Sibley, Deputy Surveyor

White Oak 22 inch diameter, bears North 88-1/2 degrees West, 203 links

UNADILLA TWP.

\* ADDITIONAL HISTORICAL INFORMATION ON BACK OF SHEET

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2 inch iron pipe.

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY  
PEER GROUP ON 9-6-00 CO. REP JED

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-07, T1N, R3E, UNADILLA, replaced existing 1/2" pipe with 1-1/4 inch break-away pipe with brass cap, stamped "Livingston Co. Monumentation Corner, P.S. 19834," 2 ft. below grade and is accepted as a careful and faithful reestablishment of the position of the original corner.

WEST 1000 FT. +/- METAL BARN - CARSONITE MARKER 7.5 FT. NORTH OF CORNER

313 DEG. 23.68' SET 1" PIPE/BRASS WITNESS CAP 2 FT BELOW GRADE IN C/L FARM LANE

045 DEG. 18.66' SET 1" PIPE/BRASS WITNESS CAP 2 FT BELOW GRADE IN C/L FARM LANE

136 DEG. 22.22' SET 1" PIPE/BRASS WITNESS CAP 2 FT BELOW GRADE IN FARM FIELD

243 DEG. 24.55' SET 1" PIPE/BRASS WITNESS CAP 2 FT BELOW GRADE IN FARM FIELD

Signed by Darrell Hughes

Date November 7, 2000

Surveyor's Michigan License No. 19834