## SURVEY & REMONUMENTATION

FEB 26 2001

SECTION	Filing Rec	RNER RECORDATION CER juirement of Act 74, Mich.	RTIFICATE PA 1970
For corners in SECTION	•	, and a state of the state of t	FILED
LIVINGSTON (County)	Located in:	Corner Code #	riceu
1. Public Land Survey	T 1N R 3E T R		2000 NOV 15 A 9: 30
2. Property Controlling in Section S. Miscellaneous Property in Sec. S.	T R		NANCY HAVILAND REGISTER OF DEEDS LIVINGSTON COUNTY, MI. 48843  LSC #1378m  Register of Deeds Stamp & File Numb
4. Lot No, Recorded 5. Private Claims	J Plat		
I, DARRELL D. HUGHES , in that under requirements of P.A. 74, I above were in conformance with resurvey instructions of the United Stat decree of a Court of Law and /or the conformance with the rules of the Mi established, re-established, monumer	n a field survey on O Michigan P.A. of 1970, the gulations and rules therefores Department of the Interioral the corner points mentical the corner points mentically and successions.	ctober 12, , 2000 do hereby corner points mentioned in lines 1 re as required in the current mar or, Bureau of Land Management coned in lines 3, 4 and 5 above we	I and 2
NOTE: Not more than 2 corners, on this certificate.	all in the same town and r	ange, may be recorded	9 29 28 27 26 25 11 12 31 32 33 34 35 36
A. Description of original monum	ent and accessories and	/or subsequent restoration:	131
GLO: 1825, Sylvester White Oak 9 in Hickory 5 inch	ch diameter, bears S	eyor outh 25 degrees East, 33 l th 9 degrees East, 5 links	UNADILLA TWP.
* ADDITIONAL HISTORI  B. Description of corner evidence	CAL INFORMATION ON e found and/or method à	BACK OF SHEET pplied in restoring or reestablis	shing corner
Found 1/2 inch iron rod			g contain.
C. Description of monument for co	orner and accessories es	tablished to perpetuate locating	g the position of the corner:
I-06, T1N, R3E, UNAD brass cap, stamped "Livir faithful reestablishment o 058 DEG. 22.45' SE 124 DEG. 22.55' SE 215 DEG. 32.85' SE	OILLA, replaced examples on Co., Monume	xisting corner with 1-1/4" ntation Corner, P.S. 1983 original corner. 10" HICKORY S 10" POPLAR S 30" OAK	"x 36" iron pipe, affixed with 2" diameter 34," and is accepted as a careful and  PA. 345 1990, APPROVED BY LIVINGSTON COUNTY PEER GROUP ON 9-6-00, CO. REP
Signed bySurveyor's Michigan License No.	lell H	Da Da	ate October 12, 2000