

**SURVEY &  
REMONUMENTATION**

**FEB 26 2001**

**SECTION**

**LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970**

For corners in

**FILED**

**2000 NOV 15 A 9:30**

**NANCY HAVILAND  
REGISTER OF DEEDS  
LIVINGSTON COUNTY, MI.  
48843**

**LSC #1382m**

**Register of Deeds Stamp & File Number**

<u>LIVINGSTON</u> (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>1N</u> R <u>3E</u>	<u>I-10</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, DARRELL D. HUGHES, in a field survey on October 12, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

**NOTE:** Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

1	A	B	C	D	E	F	G	H	I	J	K	L
2		6		5		4		3		2		1
3												
4		7		8		9		10		11		12
5												
6		18		17		16		15		14		13
7												
8		19		20		21		22		23		24
9												
10		30		29		28		27		26		25
11												
12		31		32		33		34		35		36
13												

A. Description of original monument and accessories and/or subsequent restoration:

**GLO:** 1825, Sylvester Sibley, Deputy Surveyor  
White Oak 22 inch diameter, bears South 50 degrees East, 70 links  
White Oak 32 inch diameter, bears North, 19 links

**UNADILLA TWP.**

\* ADDITIONAL HISTORICAL INFORMATION ON BACK OF SHEET

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found "MAG" nail and tag

**P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY  
PEER GROUP ON 9-6-00, CO. REP. JED**

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

**I-10, T1N, R3E, UNADILLA,** replaced existing corner with 1-1/4" x 36" iron pipe, affixed with 2" diameter brass cap, stamped "Livingston Co. Monumentation Corner, P.S. 19834," in road box and is accepted as a careful and faithful reestablishment of the position of the original corner.  
204 DEG. 26.41' SET NAIL/TAG E/S DEAD 50" MAPLE  
344 DEG. 88.03' SET NAIL/TAG E/S 26" OAK  
051 DEG. 46.51' SET NAIL/TAG SE/S 12" WALNUT  
130 DEG. 22.03' SET NAIL/TAG N/S 22" HICKORY

Signed by

*[Signature]*

Date October 12, 2000

Surveyor's Michigan License No. 19834