

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Livingston (County)	Located In:	Corner Code ##
1 Public Land Survey	T 1N R 4E	G-5
	T R	
	T R	
	T R	
2 Property Controlling in Section	S T R	
	S T R	
3 Miscellaneous Property in Sec.	S T R	
	S T R	

Register of Deeds Stamp & File Number

4 Lot No. _____, Recorded Plat _____
 5 Private Claims _____

Donald L. Bissell in a field survey on October 11, 1989, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5			4		3		2		1	
3													
4	7		8			9		10		11		12	
5							16						
6	18		17			16		15		14		13	
7													
8	19		20			21		22		23		24	
9													
10	30		29			28		27		26		25	
11													
12	31		32			33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

G-5 NW Cor. Sec. 15
 2" Well Point
 S85°W - 42.03' - 30" Hickory
 N20°W - 17.70' - 48" Oak
 N10°E - 21.05' - 45" Oak
 N65°E - 46.50' - Hickory

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-5 NW Cor. Sec. 15
 Found Witnesses, Corner removed by construction
 Set 4" x 36" Conc. Mon. w/Alum. Cap
 N85°W - 42.33' - Nail & Tag in N. Side - 30" Hickory
 N26°W - 17.70' - 48" Oak, Stump to be removed
 N27°E - 21.05' - 45" Oak, Stump to be removed
 N71°E - 46.50' - 22" Hickory

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-5 NW Cor. Sec. 15
 4" x 36" Conc. Mon. w/Alum. Cap
 N85°W - 42.33' - 30" Hickory, Nail & Tag (Boss)
 N71°E - 46.50' - 22" Hickory, Spike & Tag (Boss)
 S70°E - 94.00' - 8" Hickory, Spike & Tag (DNR)
 N4°E - 80.89' - 8" Hickory, Spike & Tag (DNR)

Signed by Donald L. Bissell Date 12-28-89
 Surveyor's Michigan License No. 18655



APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
 REVISED MAY 14, 1975
 REVISED JAN. 1983