

SURVEY &
REMONUMENTATION

FEB 24 1998

FILED

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

LIVINGSTON
(County)

Located In:

Corner Code #

1. Public Land Survey

T 1 N R 4 E

D-13

T R

T R

T R

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

1997 NOV 13 P 1:44

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

L.S.C.#790m

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

PUTNAM TWP.

I, DARRELL D. HUGHES, in a field survey on NOVEMBER 3, 19 97, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO: 1825 Sylvester Sibley, Deputy Surveyor
Black Oak 18" North 16 degrees West 35 links
Black Oak 8" South 59 degrees West 35 links

* ADDITIONAL HISTORICAL INFORMATION ON BACK OF SHEET

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 4" Diameter concrete monument with 1/2" iron pipe at Southwest corner of Lot 239 and Southwest corner of "HI-LAND LAKE SUBDIVISION NO. 4"..

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-5, T1N, R4E, PUTNAM, left 4" Diameter concrete monument with 1/2" iron pipe, affixed with 2" dia. Brass cap. Cap stamped "Livingston Co. Monumentation Corner, 19834" and is accepted as a careful and faithful reestablishment of the position of the original corner.

355 deg. Found 4" Concrete Monument (leaning Southerly) 41.70'
128 deg. Top center 4" well head 11.29'
007 deg. Southwest block foundation of house 22.74'
215 deg. Set Nail / Tag SE/S 20" Oak 23.52'
287 deg. Set Nail / Tag S/S 10" Elm 12.96'

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 9-3-97, CO. REP. JED

Signed by Darrell Hughes

Date NOVEMBER 3, 1997

Surveyor's Michigan License No. 19834

PUTNAM TOWNSHIP, T1N, R4E

D-13, SOUTH 1/4 CORNER SECTION 32, ON MICHIGAN BASE LINE.

FIELD: 12-11-1996

FOUND 4" DIAMETER CONCRETE MONUMENT WITH 1/2" IRON PIPE AT SOUTHWEST CORNER OF LOT 239 AND SOUTHWEST CORNER OF "HI-LAND LAKE SUB. NO.4", FORMER WITNESS' AGREE. I RECOMMEND, TO THE PEER GROUP, THE ACCEPTANCE OF THIS MONUMENT FOR D-13, BASED ON THE EVIDENCE TO FOLLOW:

- 1819 Joseph Wampler, U.S. Deputy Surveyor, "West on the South Boundary of Section 32, 40.00 chains, set post." P.7-7A
- 1849 Lucius Lyon, Surveyor General, compares Fletcher and Wampler base lines, shows 81 chains for mile. P.8-8E
- 1945 Clay Gordon, surveys and maps lands North and South of base line, shows corner. P.9-9B
- 1947 Lloyd Fall, surveyor from Detroit, plats "Hi-Land Lake Subdivision No.4", sets monument at this point. P.10-10A
- 1973 Dwayne Scott, DNR surveyor, surveys for encroachments along the Southerly line of "Hi-Land Lake No.4" and files Act 74. P.11-11C
- 1994 Charles Garlock, of Garlock-Smith, Inc. surveys part of Lot 250, "Hi-Land Lake Sub. No.4". He identifies corner as monument and gives witness'. P.12
- 1997 Hughes witness comparison. P.13