

SURVEY &
REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE
APR 28 1997

Nov 16 2 01 PM '94

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI
48843

For corners in

LIVINGSTON
(County)

COMMISSION

Corner Code 11

Public Land Survey T 1N R 4E G-13
T R
T R
T R
Property Controlling S T R
in Section S T R
Miscellaneous S T R
Property in Sec. S T R

L.S.C. #351m
Register of Deeds Stamp & File Number

Lot No. , Recorded Plat
Private Claims

DARRELL HUGHES, in a field survey on NOVEMBER 3, 1994,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

Description of original monument and accessories and/or subsequent restoration:

GLO: 1823 Joseph Wampler, Deputy Surveyor
Corner 'in lake'

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

PUTNAM TWP.

*Additional historical information on back of sheet
Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Corner not found, falls in lake. Re-established by the intersection of the West
line of Section 34 with the South line of Section 34 by projecting said lines as
identified in a survey by Atwell-Hicks Job No. 561-34, Book 854, Page 2, dated
May 10, 1985. Accessory irons placed on said lines near waters edge.

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

* SEE REVERSE SIDE DESCRIPTION AND ACCESSORIES.

Signed by

Darrell Hughes

Date

11-8-94

Surveyor's Michigan License No. 19834

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

P.A. 345 1980, APPROVED BY LIVINGSTON COUNTY

PEER GROUP ON 12 Oct. 94 CO. REP RLH

PUTNAM TOWNSHIP, T1N, R4E

G-13, SE CORNER SEC. 33, SW COR. SEC. 34, ON BASE LINE.

CORNER NOT FOUND. Original GLO states corner "in lake". I propose to establish the corner by intersecting the West line of Section 34 with the South line Section 34 as surveyed and identified in a survey by Atwell-Hicks. (Page 15) Reference monuments to be placed at the North and East shore of Silver Lake.

1823 Joseph Wampler, U.S. Deputy Surveyor, states "Corner Sec. 33 and 34 in Lake."

1936 Livingston County Surveyor intersected fence lines and computed corner.

1985 Atwell-Hicks finds evidence of above survey and performs survey.

G-13, T1N, R4E, PUTNAM, Corner not set, two accessories set (see sketch)
Set (2) 1" X 36" Witness pipes, affixed with 2" dia. brass cap, stamped "Livingston Co. Witness Corner"

Witness pipe at north shore Silver Lake on G-13/G-12 line.

145 DEG. 12.43' SET NAIL/TAG S/S 8" OAK.

350 DEG. 14.01' SET NAIL/TAG SW/S 24" OAK.

293 DEG. 35.22' SET NAIL/TAG S/S 12" OAK.

325 DEG. 44.72' SET NAIL/TAG W/S 9" OAK.

180 DEG. 17' WATERS EDGE

Witness pipe at east shore Silver Lake on G-13/ H-13 line.

187 DEG. 85.28' SET NAIL/TAG W/S UTILITY POLE.

332 DEG. 10.53' SET NAIL/TAG SW/S 10" ELM.

116 DEG. 9.65' SET NAIL/TAG N/S 36" POPLAR.

223 DEG. 125.80' SET NAIL/TAG E/S 36" SYCAMORE (AT WATER EDGE)

270 DEG. 20' WATERS EDGE.

090 DEG. CL GRAVEL DRIVE.

