

FILED

9

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

OCT 16 11 44 AM '95

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI
48843

corners in

LIVINGSTON
(County)

Located In:

Corner Code ##

Public Land Survey

T 1N R 4E

I-10

T R

T R

T R

Property Controlling

S T R

in Section

S T R

Miscellaneous

S T R

Property in Sec.

S T R

L.S.C. # 502m

Register of Deeds Stamp & File Number

Lot No. , Recorded Plat

Private Claims

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

PUTNAM TWP.

SURVEY &
REMONUMENTATION

NOV 27 1995

COMMISSION

Description of original monument and accessories and/or subsequent restoration:

GLO: 1823, Joseph Wampler, Deputy Surveyor

Black Oak 14", South 43 degrees West, 19 links

White Oak 13", North 41 degrees West, 40 links

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2 inch iron pipe

*Additional descriptions and historical information on back of this sheet.

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-10, T1N, R4E, PUTNAM, replaced existing corner with 1-1/4" X 36" iron pipe, affixed with 2" dia. brass cap, all within a road box, cap stamped "Livingston Co. Monumentation Corner, P.S. 19834, and is accepted as a careful and faithful reestablishment of the position of the original corner.

227 DEG. 47.44' SET NAIL/TAG NW/S UTILITY POLE.

274 DEG. 26.38' SET NAIL/TAG S/S UTILITY POLE.

096 DEG. 48.24' SET NAIL/TAG S/S UTILITY POLE.

149 DEG. 51.54' SET NAIL/TAG SW/S 16" SPRUCE.

Signed by

Date October 5, 1995

Surveyor's Michigan License No. 19834

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY

9-1-95

15N

PUTNAM TOWNSHIP, T1N, R4E

I-10, EAST 1/4 CORNER SEC. 27 AND WEST 1/4 CORNER SEC. 26

FIELD: JANUARY 1995

FOUND 1/2" IRON PIPE, ABOVE POINTED STONE, IN CENTERLINE SOUTH HOWELL ROAD (PATTERSON LAKE ROAD) AND 22' NORTH OF CENTERLINE DeLAPP LANE TO WEST. 0.2' BELOW ASPHALT ROAD GRADE. MEASURES NORTH TO I-9 AGREE WITH ROSS, BOSS AND THOMPSON. EAST TO J-10, BENTON AND ROSS AGREE. SOUTH TO I-11, HUGHES AND BENTON VARY BY 1'. WITNESS' AGREE WITH THOMPSON AND BOSS. GOOD FOR GPS.

1823 Corner first set by Joseph Wampler, U.S. Deputy Surveyor.... "North between 26 and 27, 40.00 chains, set 1/4 sec. post." P.7

1870 Miles Bullock resets corner at "equidistant" between I-9 and I-11 (40.125 chains, 2648.25') P.8

1871 Miles Bullock uses corner to divide Sec. 26. P.9

1913 County surveyor Sec.27 corner witness history P.10

1955 John C. Miller plats "Carol-Don Heights No.1" P.11

1963-1972 Munsell and Garlock survey notes Sec. 27 P12-12C

1972 Charles Wilson survey and Act 74. P. 13-13A

1972 Robert Jagow files Act 74. P14

1972 Charles Garlock survey and Act 74. P. 15-15A

1975 Francis Papke files Act 74. P.16-16A

1976 Charles Garlock surveys. P.17-17A

1981 Patrick Benton survey. P.18-18A

1983 Gary Boss survey and Act 74. P.19-19A

1990 Brad Thompson survey and Act 74. P.20-20A

1990 Donald Ross survey. P. 21-21B

1994 Herbert Munzel survey P.22

1994 Gary Boss survey. P.23-23A

1995 Garlock witness file P.24

1995 Hughes remon. witness comparison P.25-25B