

FILED

9-

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

LIVINGSTON
(County)

Located in:

Corner Code #

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

1. Public Land Survey

T1N R4E K-8
T R
T R
T R
T R
S T R
S T R
S T R
S T R

2. Property Controlling
in Section

3. Miscellaneous
Property in Sec.

L.S.C.#572m

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, DARRELL HUGHES, in a field survey on 11-8, 19 96 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO: 1823
Black Oak 13", South 31 degrees West, 245 links
Black Oak 13", South 09 degrees East, 241 links

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 3/4" iron pipe set by Atwell-Hicks in 1972

*Additional descriptions and historical information on back of this sheet.

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 9-18-96 CO. REP JED

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-8, T1N, R4E, PUTNAM, replaced existing corner with 1-1/4" X 36" iron pipe, affixed with 2" dia. brass cap, stamped "Livingston Co. Monumentation Corner, P.S. 19834, and is accepted as a careful and faithful perpetuation of the position of the original corner.
156 DEG. 9.78' SET NAIL/TAG SW/S TWIN 10" BOX ELDER.
187 DEG. 41.47' SET NAIL/TAG E/S 12" ELM.
295 DEG. 28.59' SET NAIL/TAG NE/S 20" WILLOW.
321 DEG. 21.70' SET NAIL/TAG SW/S 64" WILLOW.

Signed by Amell Hicks
Surveyor's Michigan License No. 19834

Date November 8, 1996

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983
REVISED OCT., 1995

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7			8		9		10		11		12	
5													
6	18			17		16		15		14		13	
7													
8	19			20		21		22		23		24	
9													
10	30			29		28		27		26		25	
11													
12	31			32		33		34		35		36	
13													

PUTNAM

PUTNAM TOWNSHIP, T1N, R4E

K-8, WEST 1/4 COR. SEC. 24 AND EAST 1/4 COR. SEC. 23

FIELD: 5-10-1996

FOUND 3/4" IRON PIPE AND CAP (NOT LEGIBLE) IN LOW AREA. WITNESS' AGREE FROM PAST RECORDS. 3/4" PIPE SET BY ATWELL-HICKS IN 1972. SEE PAGE 9 FOR METHOD USED IN SETTING. BOSS, BENTON, GARLOCK, DESINE AND HUGHES HAVE USED THIS PIPE FOR PAST SURVEYS. MEASURES NORTH TO K-7 AND SOUTH K-9 AGREE WITH PAST MEASURES. I RECOMMEND TO THE PEER GROUP THIS PIPE FOR THE LOCATION AND PERPETUATION OF K-8.

1823 Corner first set by Joseph Wampler, U.S. Deputy Surveyor.....North between 23 & 24, 40 chains, set post. P.7

1972 Atwell-Hicks sets corner in survey at proportionate distance and on line with found irons and files Act 74. P.8-9

1973 Atwell-Hicks survey uses iron, transposes distance for witness' (28.5' to 25.5') P. 10

1975 Garlock survey "in swamp-not found" P.11

1975 Garlock survey copies Atwell-Hicks witness' P.12

1977 Benton copies Atwell-Hicks witness' P.13

1977 Boss survey copies witness', P.14

1978 Boss survey. P.15

1979 Boss survey P.16

1982 Boss survey P.17

1983 Boss survey P.18

1984 Boss survey P. 19

1988 Boss survey P. 20

1988 Benton survey, no witness' P.21

1988 Boss survey. P.22

1988 Boss survey. P.23

1988 Boss survey P.24 A-B

1990 Boss survey P.24 C-D

1990 Garlock survey P.25

1991 Hughes survey. field measured witness' P.26

1992 Desine survey field measures witness' P.27

1994 Desine survey P.28

1996 Hughes remon witness' P.29