

SURVEY &  
REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

9

FILED

For corners in

LIVINGSTON Located In: Corner Code #  
(County)  
1. Public Land Survey T 1 N R 4 E H-05  
T    R     
T    R     
T    R     
2. Property Controlling S    T    R     
in Section S    T    R     
3. Miscellaneous S    T    R     
Property in Sec. S    T    R   

2000 SEP 28 A 9:18

NANCY HAVILAND  
REGISTER OF DEEDS  
LIVINGSTON COUNTY, MI.  
48843

LSC #1281m

Register of Deeds Stamp & File Number

4. Lot No.           , Recorded Plat             
5. Private Claims           

I, JACK K. SMITH, in a field survey on AUGUST 25, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2		6		5		4		3		2		1
3												
4		7		8		9		10		11		12
5												
6		18		17		16		15		14		13
7												
8		19		20		21		22		23		24
9												
10		30		29		28		27		26		25
11												
12		31		32		33		34		35		36
13												

A. Description of original monument and accessories and/or subsequent restoration:

GLO 1825 JOSEPH WAMPLER SET POST  
TAMARACK 20" N66°W 12.54'  
TAMARACK 5" S01°W 17.82'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

THE EXISTING CORNER IS A 1/2" x 5' REROD SET AT 1/2 DISTANCE ON LINE BETWEEN G-05 AND I-05 BY BRAD THOMPSON IN 1993 IN A SWAMP. DISTANCES COMPARE WELL TO THE WEST. THIS POSITION APPEARS TO BE THE ONLY ONE USED SINCE IT WAS SET IN 1993.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:


H-05 NORTH 1/4 CORNER SECTION 15, T1N, R4E, PUTNAM TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN:  
SET 1 1/4" x 36" STEEL PIPE WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP STAMPED SURVEYOR #35999 IN PLACE OF THE 1/2" REROD. \*\*NOTE: THERE IS ABUNDANT POISON SUMAC SURROUNDING THIS CORNER !!

S45°E SPIKE AND REMON TAG ON WEST SIDE OF 8" ELM 41.50'  
S45°E 1" STEEL REMON WITNESS PIPE AND BRASS CAP 10.00'  
N10°W 1" STEEL REMON WITNESS PIPE AND BRASS CAP 10.00'  
S40°W 1" STEEL REMON WITNESS PIPE AND BRASS CAP 10.00'

Signed by 

Date 9-15-2000

Surveyor's Michigan License No. 35999



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS JAN. 22, 1971

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY

REVISED MAY 14, 1975

REVISED JAN., 1983

REVISED OCT., 1995

PEER GROUP ON 2.2-2000 CO. REP JED