

228269 OCT 10 1995

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

OCT 11 10 28 AM '95
NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI
48843

FILED

For corners in
Livingston

(County)

Located In:

Corner Code: #

1. Public Land Survey

T 1N R 6E

I-10

T R

T R

T R

T R

2. Property Controlling
In Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

L.S.C. #477m

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I. Gary R. Boss in a field survey on 10-4-95

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

Linden 14" N 28° E 41 links

Elm 9" N 63° W 53 links

Willow 6" bent to south planted by Arthur Bennett - 1923 Grant Dunning

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Relocated from lot corners and monumentation

found in Greenway Subdivision Liber 9 - Pages 49-50

Livingston County Records

SURVEY &
REMONUMENTATION

NOV 27 1995

COMMISSION

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Witness Corner

36" pipe with brass cap set 35 feet North of
section corner & 15 feet west of edge of canal
8.68' N 5° W nail & tag southwest side 22" Cedar

17.19' S 40° W nail & tag in south side 12"

Cottonwood

15.88' S 5° E nail & tag in west side 16" Oak

15.61' east nail & tag in North side 6" multiple Elm

Witness Corner

Set 36" pipe with brass cap

East of section corner 180.00 feet

38.10' N 18° W nail & tag in S.W. side 26"

Cottonwood

52.48' N 5° E nail & tag in west side 10" Elm

53.05' S 2° W nail & tag in west side 26" multiple

Maple

73.65' S 60° W nail & tag in south side 22" multiple

Maple

Signed by Gary R. Boss

Date 10/6/95

Surveyor's Michigan License No. 17022

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 9-20-95 CO. REP JED



SUMMARY

I-10

WEST 1/4 CORNER, SECTION 26, T1N-R5E, GREEN OAK TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN

-Corner Obliterated-

Original survey by Alex Holmes in 1816. Lyle Munsell field notes on page 10, this dossier, indicates he found 1 1/2" pipe 5 feet north of canal from proposed plat of Green Way Subdivision. Munsell's survey on 5-14-58 finds distance of 2705.30 feet to center of Section 26. This distance is also found on unrecorded plat of Driver's Subdivision. On 1-3-95, Boss Engineering computed this corner by utilizing irons found on L.N. Hayden's R.L.S. Plat of Green Way Subdivision. The distance Easterly to the center of Section was calculated to be 2703.72 feet in comparison to Munsell's distance of 2705.3 feet. Therefore, we recommend placement of West 1/4 corner of Section as computed by irons found in Green Way Subdivision.

SUMMI10