

# SURVEY & REMONUMENTATION

FEB 26 2001

FILED

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

### SECTION

For corners in  
LIVINGSTON  
(County)

Located in: GREEN OAK Corner Code #

2000 OCT 19 A 10:31

NANCY HAVILAND  
REGISTER OF DEEDS  
LIVINGSTON COUNTY, MI.  
48843

1. Public Land Survey T 1N R 6E C-5  
T R  
T R  
T R
2. Property Controlling S T R  
in Section S T R
3. Miscellaneous S T R  
Property in Sec. S T R
4. Lot No. , Recorded Plat
5. Private Claims

9' LSC #1301m  
Register of Deeds Stamp and File Number

I, Bryan L. Boss, in a field survey on APRIL 7, 2000, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefor as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below.

**NOTE:** Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

**A. Description of original monument and accessories and/or subsequent restoration:**

1823 BY S. SIBLEY, DEPUTY SURVEYOR  
SET POST  
W. OAK 12" N 87 1/2° E 80 LINKS  
W. OAK 23" N 3° W 1.17 CHAINS

**B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:**

FOUND 1/2" IRON IN A MONUMENT BOX IN CENTER LINE RICKETT ROAD


**C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:**

SET 1 1/4" X 30" STEEL PIPE WITH 6" X 1 1/4" BREAKAWAY PIPE AND BRASS CAP STAMPED "LIVINGSTON COUNTY REMONUMENTATION CORNER" IN EXISTING MONUMENT BOX.  
EAST 31.15' TO CENTER 6" FENCE POST  
S 65°E 34.10' TO 19" OAK REMON NAIL/TAG SW/SIDE  
S 25°E 66.98' TO 22" OAK REMON NAIL/TAG NE/SIDE  
WEST 31.05' TO CENTER 6" FENCE POST

SOUTH 7.98' FOUND 1" PIPE  
N 75°W 31.30' TO 30" OAK REMON NAIL/TAG S/SIDE  
N 20°W 71.80' TO 16" OAK REMON NAIL/TAG E/SIDE

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY  
PEER GROUP ON 4-5-2000, CO. REP SED



Signed by Bryan L. Boss

Date Sept. 5, 2000

Surveyor's Michigan License No. 29238