

SURVEY &
REMONUMENTATION

FEB 25 1999

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in SECTION

LIVINGSTON
(County)

Located In:

Corner Code #

1. Public Land Survey T 2 N R 3 E K-9
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

1998 OCT 14 P 2:12

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

9

LSC 916M
Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, DARRELL D. HUGHES, in a field survey on OCTOBER 6, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

IOSCO TWP.

A. Description of original monument and accessories and/or subsequent restoration:

GLO: 1825 Sylvester Sibley, Deputy Surveyor
Tamarack 5" North 25 degrees West 27 links
Black Ash 8" South 70½ degrees West 4 links

* ADDITIONAL HISTORICAL INFORMATION ON BACK OF SHEET

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Corner not found. Determined corner lost. Reconstructed position by double proportionate measures.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-9, T2N, R3E, IOSCO, set corner with 1¼" x 36" iron pipe, affixed with 2" dia. Brass disk.
Disk stamped "Livingston Co. Monumentation Corner, 19834" and is accepted as a careful and faithful reestablishment of the position of the original corner.

024 deg. Set Nail / Tag E/S 45" Maple Cluster 88.43'
100 deg. Set Nail / Tag N/S 18" Oak 159.19'
153 deg. Set Nail / Tag SW/S 20" Dead Tree 65.33'
155 deg. Set Nail / Tag SW/S 10" Maple 36.62'
270 deg. Top of East bank of a 20 ft. wide North-South ditch. ±10'

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 5-20-98, or JED

Signed by

[Signature]

Date OCTOBER 6, 1998

Surveyor's Michigan License No. 19834