

SURVEY &  
REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in

LIVINGSTON

(County)

Located In:

Corner Code #

1. Public Land Survey

T 2 N R 3 E

E-07

T      R     

T      R     

T      R     

2. Property Controlling  
in Section

S      T      R     

S      T      R     

3. Miscellaneous  
Property in Sec.

S      T      R     

S      T      R     

2000 NOV 15 A 9:29

NANCY HAVILAND  
REGISTER OF DEEDS  
LIVINGSTON COUNTY, MI.  
48843

LSC #1366m

9' Register of Deeds Stamp & File Number

4. Lot No.         , Recorded Plat                     

5. Private Claims                                             

I, DARRELL D. HUGHES, in a field survey on October 31, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

GLO: 1825, Sylvester Sibley, Deputy Surveyor  
White Oak 10 inch diameter, bears South 01 degree East, 650 links

IOSCO TWP.

\* ADDITIONAL HISTORICAL INFORMATION ON BACK OF SHEET

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2 inch iron rod

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-07, T2N,R3E, IOSCO, replaced existing corner with 1-1/4" x 36" iron pipe, affixed with 2" diameter brass cap, stamped "Livingston Co. Monumentation Corner, P.S. 19834," and is accepted as a careful and faithful reestablishment of the position of the original corner.

110 DEG. 22.94' SET NAIL/TAG S/S 14" OAK

155 DEG. 5.95' SET NAIL/TAG E/S 8" OAK

010 DEG. 21.66' SET NAIL/TAG E/S 40" OAK

280 DEG. 7.04' SET NAIL/TAG N/S 10" CHERRY

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY  
PEER GROUP ON 9-20-00 CO. REP JED

Signed by

*Darrell Hughes*

Date October 31, 2000

Surveyor's Michigan License No. 19834