

# SURVEY & REMONUMENTATION

FEB 26 2001

## SECTION

For corners in

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

LIVINGSTON

(County)

Located In:

Corner Code #

1. Public Land Survey

T 2 N R 3 E

E-08

2. Property Controlling  
in Section

S

T

R

E

3. Miscellaneous

S

T

R

E

Property in Sec.

S

T

R

E

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

FILED

2000 NOV 15 A 9:29

NANCY HAVILAND  
REGISTER OF DEEDS  
LIVINGSTON COUNTY, MI.  
48843

LSC #1367m

Register of Deeds Stamp & File Number

I, DARRELL D. HUGHES, in a field survey on October 25, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2		6		5		4		3		2		1
3												
4		7		8		9		10		11		12
5												
6		18		17		16		15		14		13
7												
8		19		20		21		22		23		24
9												
10		30		29		28		27		26		25
11												
12		31		32		33		34		35		36
13												

IOSCO TWP.

A. Description of original monument and accessories and/or subsequent restoration:

GLO: 1825, Sylvester Sibley, Deputy Surveyor  
Black Oak 6 inch diameter, bears North 38-1/2 degrees East, 18 links  
Black Oak 5 inch diameter, bears South 36 degrees East, 28 links

\* ADDITIONAL HISTORICAL INFORMATION ON BACK OF SHEET

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 3/4 inch iron pipe

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-08, T2N, R3E, IOSCO, replaced existing corner with 1-1/4" x 36" iron pipe, affixed with 2" diameter brass cap, stamped "Livingston Co. Monumentation Corner, P.S. 19834," and is accepted as a careful and faithful reestablishment of the position of the original corner.  
299 DEG. 78.50' SET NAIL/TAG S/S 9" THORN APPLE  
226 DEG. 35.48' SET NAIL/TAG SW/S 9" ASH  
178 DEG. 20.82' SET NAIL/TAG E/S 10" DOGWOOD  
126 DEG. 50.69' SET NAIL/TAG NE/S 7" PINE

PA. 345 1990, APPROVED BY LIVINGSTON COUNTY  
PEER GROUP ON 9-20-00 CO. REP LES

Signed by

Surveyor's Michigan License No.

19834

Date

October 25, 2000