

SURVEY & MONUMENTATION

FEB 26 2001

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in **SECTION**

LIVINGSTON

(County)

Located In:

Corner Code #

1. Public Land Survey

T 2 N R 3 E

F-07

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

2000 NOV 15 A 9:29

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

LSC #1370m

Register of Deeds Stamp & File Number

I, DARRELL D. HUGHES, in a field survey on October 25, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO: 1825, Sylvester Sibley, Deputy Surveyor

White Oak 20 inch diameter, bears North 27-1/2 degrees West, 79 links

White Oak 18 inch diameter, bears South 16 degrees East, 89 links

* ADDITIONAL HISTORICAL INFORMATION ON BACK OF SHEET

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 3/4 inch iron pipe

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-07, T2N, R3E, IOSCO, replaced existing corner with 1-1/4" x 36" iron pipe, affixed with 2" diameter brass cap, stamped "Livingston Co. Monumentation Corner, P.S. 19834," and is accepted as a careful and faithful reestablishment of the position of the original corner.

273 DEG. 26.84' SET NAIL/TAG N/S 18" CHERRY

022 DEG. 30.00' SET NAIL/TAG E/S 12" CHERRY

015 DEG. 13.00' SET NAIL/TAG E/S 42" OAK

095 DEG. 42.01' SET NAIL/TAG N/S 18" HICKORY

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY

PEER GROUP ON 9-20-00 CO. REP JED

Signed by

Darrell Hughes

Date October 25, 2000

Surveyor's Michigan License No. _____

19834

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

REVISED MAY 14, 1975
REVISED JAN. 1983
REVISED OCT. 1995

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

IOSCO TWP.