

**SURVEY &  
REMONUMENTATION**

**FEB 26 2001**

**LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970**

**FILED**

2000 NOV 15 A 9:30

NANCY HAVILAND  
REGISTER OF DEEDS  
LIVINGSTON COUNTY, MI.  
48843

LSC #1373m

9' Register of Deeds Stamp & File Number

For corners in **SECTION**

<u>LIVINGSTON</u> (County)	Located In:	Corner Code #
1. Public Land Survey	<u>T 2 N R 3 E</u>	<u>G-08</u>
	T <u>    </u> R <u>    </u>	<u>    </u>
	T <u>    </u> R <u>    </u>	<u>    </u>
	T <u>    </u> R <u>    </u>	<u>    </u>
2. Property Controlling in Section	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>
	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>
3. Miscellaneous Property in Sec.	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>
	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, DARRELL D. HUGHES, in a field survey on October 25, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2	6		5			4		3		2		1
3												
4	7		8			9		10		11		12
5												
6	18		17			16		15		14		13
7												
8	19		20			21	●	22		23		24
9												
10	30		29			28		27		26		25
11												
12	31		32			33		34		35		36
13												

**IOSCO TWP.**

A. Description of original monument and accessories and/or subsequent restoration:

**GLO:** 1825, Sylvester Sibley, Deputy Surveyor  
White Oak 30 inch diameter, bears North 11 degrees East, 178 links  
White Oak 26 inch diameter, bears North 78-1/2 degrees East, 316 links

\* ADDITIONAL HISTORICAL INFORMATION ON BACK OF SHEET

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2" iron rod.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

**G-08, T2N, R3E, IOSCO,** replaced existing corner with 1-1/4" x 36" iron pipe, affixed with 2" diameter brass cap, stamped "Livingston Co. Monumentation Corner, P.S. 19834," and is accepted as a careful and faithful reestablishment of the position of the original corner.

- 040 DEG. 89.00' SET NAIL/TAG W/S 9" MAPLE
- 116 DEG. 114.27' SET NAIL /TAG N/S 14" MAPLE CLUSTER
- 244 DEG. 52.86' SET NAIL/TAG N/S 22" MAPLE
- 350 DEG. 65.13' SET NAIL/TAG E/S 24" OAK
- 330 DEG. 1.83' FOUND 1/2" IRON ROD

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY  
PEER GROUP ON 9-20-00, CO. REP LED

Signed by Darrell Hughes  
Surveyor's Michigan License No. 19834

Date October 25, 2000