

**SURVEY &  
REMONUMENTATION**

FEB 25 1999

**SECTION**

**LAND CORNER RECORDATION CERTIFICATE**  
Filing Requirement of Act 74, Mich. P.A. 1970

**FILED**

For corners in  
LIVINGSTON

(County)

Located In:

Corner Code #

1. Public Land Survey

T	2N	R4E	I4
T	—	R	—
T	—	R	—
T	—	R	—
S	—	T	—
S	—	T	—
S	—	T	—
S	—	T	—

2. Property Controlling  
in Section

3. Miscellaneous  
Property in Sec.

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

1998 AUG 20 P 4: 46

NANCY HAVILAND  
REGISTER OF DEEDS  
LIVINGSTON COUNTY, MI.  
48843

L.S.C. #892m

Register of Deeds Stamp & File Number

I, CHARLES E GARLOCK, in a field survey on AUG 12, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO SURVEY DATED APRIL 15, 1825 BY S SIBLEY

GLO WITNESSES: TAM15-N85W-9 LKS

B ASH 7-S57½E-4 LKS

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2" I. ROD AT THE INTERSECTION OF VERY OLD REMAINS OF FOUR FENCE LINES TO THE NORTH, SOUTH, EAST AND WEST.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I4: E 1/4 COR. SEC. 10, T2N-R4E, MARION TWP. LIV. CO. MI; REPLACED 1/2" I. ROD WITH 1 1/4" X 36" I. PIPE WITH LIV. CO. REMON BRASS CAP ON TOP.  
N47W-40.02'-SP & TAG N/S 18" OAK  
S76W-15.75'-SP & TAG N/S 22" HICKORY  
S15E-32.25'-SP & TAG N/S 9" MAPLE  
N41E-6.14'-SP & TAG E/S 7" BASSWOOD

CARSONITE POST NEXT TO CORNER

Signed by

Surveyor's Michigan License No. 14762

Date AUGUST 13, 1998

PA. 345 1980, APPROVED BY LIVINGSTON COUNTY  
PEER GROUP ON 5/20/98 CO. REP VED

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN. 1983  
REVISED OCT. 1995

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

