

SURVEY & REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in

LIVINGSTON
(County)

Located In:

Corner Code #

2000 NOV -8 A 9:43

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

LSC #1348m

Register of Deeds Stamp & File Number

1. Public Land Survey

T___ R___
T___ R___
T___ R___
T___ R___

2. Property Controlling
in Section

S 28/29 T 2N R 4E 003

3. Miscellaneous
Property in Sec.

S 28/29 T 2N R 4E 003 ✓

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, JACK K SMITH, in a field survey on OCT 4, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

GLO 1825 SIBLEY SET POST ON NORTH SIDE OF LAKE (MEANDER CORNER)
BLACK ASH 22" N38°E 1.76 CH
BLACK ASH 20" N08°W 2.26 CH

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

THE MEANDER CORNER IS CURRENTLY MARKED BY A 1/2" REROD SET IN AUGUST, 2000 BY JACK K. SMITH AT THE PRORATED GLO DISTANCE BETWEEN E-09 AND E-11.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

003
MEANDER CORNER SOUTH OF E-09 ON THE SECTION LINE BETWEEN SECTIONS 28 AND 29, T2N, R4E, MARION TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN:
REPLACED 1/2" REROD WITH 1 1/4" X 36" STEEL PIPE WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP WITH SURVEYOR #35999 AND CARSONITE POST.

N50°E SPIKE AND LIV. COUNTY REMON TAG IN NW SIDE OF 6" CHERRY 36.33'
NORTH SPIKE AND LIV. COUNTY REMON TAG IN E SIDE OF 6" MAPLE 38.95'
S30°E SPIKE AND LIV. COUNTY REMON TAG IN E SIDE OF 6" CHERRY 19.58'
S85°W SPIKE AND LIV. COUNTY REMON TAG IN S SIDE OF 14" MAPLE 56.72'

Signed by [Signature]

Date 10-26-2000

Surveyor's Michigan License No. 35999



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN 28, 1971
REVISED MAY 14, 1975 REVISED JAN, 1983

REVISED OCT, 1995

PA 345 1990, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 9-20-2000 CO. REP JED