SURVEY & REMONUMENTATION

FEB 2 6 2001

10	Seren	CT	* F	* # E
	-		14	311

LAND CORNER RECORDATION CERTIFICATE nt of Act 74, Mich. P.A. 1970

1 9

-	ŧ	1	۳	•	Г
F	I	1	r	٠	ı
1	ŧ	Ł	L		L

2000	NOV	291A	q:	50

	SECTION	Filing Requireme
For corners in		

L	IVINGSTON		Located in: GENOA	Corner Code #	CICA DIAMETER AND
	(County)		Ecoution III.		NANCY HAVILAND PERISTER OF DEEDS
1.	Public Land Survey		T 2N R 5E	G-7	NANCY HAVILAND REGISTER OF DEEDS LIVINGSTON COUNTY, MI. 48843
			T R		40.70
			T R		
			TR		
2.	Property Controlling	S	TR		L CO. #1200
	in Section	s	TR	· · · · · · · · · · · · · · · · · · ·	LSC #1390m
3.	Miscellaneous	s	T R		Register of Deeds Stamp and File Number
	Dunmanto in Can	-	-		riegister or becas other dia the realison

~~	: #	111	n	∩
`	∓ ∓		14	E 115

Lat Na Departed Dist :

		,	_
5.	Private Claims		

l, Bryan L. Boss	, in a field surve	v on FEI	BRUARY 15, 2000	
do hereby certify to in lines 1 and 2 a	hat under requirements of P. above were in conformance survey instructions of the	A. 74, Michigan P.A. e with regulations ar	of 1970, the corner nd rules therefor	er points mentioned as required in the
Management or by above were in co	a decree of a Court of Lav nformance with the rules o stablished, re-established,	v and/or that the corne f the Michigan Board (er points mentione of Land Surveyors	d in lines 3,4 and to or by a Decree of
expressed below.	stablished, le-established,		munienteu, recu	vereu, round as

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1823 BY S. SIBLEY, DEPUTY SURVEYOR SET POST W. OAK 12" S 12 1/2" W 43 LINKS W. OAK 10" N 8 1/2" W 19 LINKS

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: FOUND 1/2" IRON ROD IN INTERSECTION OF CROOKED LAKE & FISHBECK RDS

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 1 1/4" X 12" STEEL PIPE WITH 6" BREAKAWAY PIPE & A BRASS CAP STAMPED "LIVINGSTON COUNTY REMONUMENTATION CORNER" IN MONUMENT BOX OVER CULVERT N 10° E 105.17" SET REMON NAIL/TAG W/SIDE 28" OAK S 60° E 85.58' SET REMON NAIL/TAG N/SIDE 19"

N 10° W 72.22' SET REMON NAIL/TAG E/SIDE 20" MAPLE

Date

CHERRY S 45° W 81.97' SET REMON NAIL/TAG N/SIDE 6"

WHITE PINE

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY PEER GROUP ON 2-2-2000 CO. REP JED

MICHIQ BRYAN L. BOSS and Surveyor NO. 29238 SED LAND

Signed by	A Ton
Surveyor's Michigan License No	29238