

SURVEY & REMONUMENTATION

FEB 26 2001

FILED

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

2000 NOV 29 A 9:50

For corners in
LIVINGSTON
(County)

Located in: GENOA

Corner Code #

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

- | | | | |
|------------------------------------|------|------|-----|
| 1. Public Land Survey | T 2N | R 5E | H-7 |
| | T | R | |
| | T | R | |
| | T | R | |
| 2. Property Controlling in Section | S | T | R |
| | S | T | R |
| 3. Miscellaneous | S | T | R |
| Property in Sec. | S | T | R |

LSC #1392m

Register of Deeds Stamp and File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, Bryan L. Boss, in a field survey on MARCH 23, 2000, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefor as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below.

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

- A. Description of original monument and accessories and/or subsequent restoration:

1823 BY S. SIBLEY, DEPUTY SURVEYOR
SET POST
TAMARACK 14" N 14°W 3 LINKS
TAMARACK 10" SOUTH 7 LINKS

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2" IRON IN CENTERLINE CROOKED LAKE ROAD
BELOW 1/2" IRON FOUND 3/4" PIPE & A STONE

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 1 1/4" X 18" STEEL PIPE WITH A BRASS CAP
STAMPED "LIVINGSTON COUNTY
REMONUMENTATION CORNER" IN A MONUMENT
BOX ABOVE A STONE
NORTH 58.32' SET REMON NAIL/TAG W/SIDE P.
POLE
N 57°E 60.85' SET REMON NAIL/TAG S/SIDE 24"
CHERRY
S 75°E 74.67' SET REMON NAIL/TAG N/SIDE 20"
OAK
SOUTH 52.08' SET REMON NAIL/TAG E/SIDE P.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 2-2-2000 CO. REP JED



Signed by Bryan L. Boss

Date Sept. 5, 2000

Surveyor's Michigan License No. 29238