SURVEY & REMONUMENTATION

FILED

FEB 26 2001

LAND CORNER RECORDATION CERTIFICATE

2000	nrt	19	Λ	in:	30

For corners in SECTION	ON Filing Requirement of Act 74, Wich. P.A. 197	0 20	180 UCI	17	A 10	٠ ي	
LIVINGSTON (County)	Located in: BRIGHTON Corner Code #		NANCY REGIST	ER OF	DEED	\$	
Public Land Survey	T R B B-7	Li	VINSTI	ON CO 18843	UNIY.	MI.	
 Property Controlling in Section Miscellaneous 	STR	LSC #1		and F	ile Nu	mber	
Property in Sec.	S 18 T 2N R 6E 004						
4. Lot No	, Recorded Plat						
5. Private Claims		<u>A_B</u> _	CDE	F G	<u>H</u>	 	-
	•	2			ş	<u> </u> -	{-
		3	+++			┝╌┼╼	┵
Bryan L. Boss	, in a field survey on MAY 30,2000	, 4	│ ┇╼┩	ļ	-10	<u>-1</u> 1-	-12
do hereby certify that under	r requirements of P.A. 74, Michigan P.A. of 1970, the corner points mention	* 1	╀╌┼			┝╌┼╴	╂┼
	ere in conformance with regulations and rules therefor as required in the instructions of the United States Department of the Interior, Bureau of La	fi 10	+5 $+$	-16-	-15-	-14-	- - i3
	of a Court of Law and/or that the corner points mentioned in lines 3,4 an	1 1	 			\vdash	+
	ce with the rules of the Michigan Board of Land Surveyors or by a Decree of		1-20-	-21 -	-22-	23-	24
Court of Law; established expressed below.	d, re-established, monumented, re-monumented, recovered, found a	³ 9 	╀			╟┼	++
•	1 corners all in the same town and range, may be recorded	10 -30-	 	-28-	-27-	-26	
NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.			╂╌╂╼╌┟	+-		├-	++
		12 -31 -	1-32-	-33-	-34-	<u></u> −35 ·	3€
A. Description of origin	nal monument and accessories and/or subsequent restoration:	13	111				
PRAIRIE	POST IN WEST MARGIN OF	•					
W. OAK 30" S 71°W 1. W. OAK 12" N12°W 1.							

Description of corner evidence found and/or method applied in restoring or reestablishing corner: THIS CORNER IS NOW IN WOODLAND LAKE

TWO REFERENCE POINTS WERE ESTABLISHED. ONE NORTH AND ONE WEST OF THE CORNER

(603) B-7 TO NORTH REF. PT. N02°36'43'W, 134.52' (604) B-7 TO WEST REF. PT. S87°32'04'W, 143.00' NORTH PT TO WEST PT. S44°12'50'W 196.07

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

NORTH REFERENCE POINT (OC3) SET 1 1/4" X 36" STEEL PIPE WITH BRASS CAP STAMPED "LIVINGSTON COUNTY REMONUMENTATION WITNESS" N45°E 3.78' SET REMON N/T NW/SIDE 12" W. OAK NORTH 10.05' SET REMON N/T SW/S 12" W. OAK N84°W 27.94' SET REMON N/T SE/S 12" W. OAK

WEST REFERENCE POINT (004) SET BRASS CAP STAMPED "LIVINGSTON COUNTY REMONUMENTATION WITNESS" ON TOP OF EXISTING CONCRETE MONUMENT N30°W 42.72' SET REMON NAIL/TAG S/SIDE 24" WHITE OAK N60°W 4.0.' SET REMON NAIL/TAG S/SIDE 8" OAK NORTH 31.51' SET NAIL/TAG SW/SIDE 18" OAK N15°E 22.75' SET NAIL/TAG W/SIDE 12" WHITE OAK

\$19°W 8.59' SET REMON NAIL/TAG SW/SIDE 18" WHITE OAK

4-5-2000 CO. NET.

OF MICHIG BRYAN L 8088 nd Surveyor NO. 29238 LAND

Signed by	1/2m
Surveyor's Michigan License No.	29238

2000