SURVEY & REMONUMENTATION

FEB 26 2001

FILED

9	-	CT	IC	ì
~	_	~ .		

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

	r corners in		•	1	i	000	OCT 1	9	ΔΙ	n: 3	1		
	IVINGSTON	Located in: BRIGHT	TON Corner Code	#							, i		
1.	(County) Public Land Survey	T 2N R 6E B-9				NANCY HAVIL AND REGISTER OF DEEDS LIVINGSTON COUNTY, MI. 48843							
2. 3.	Property Controlling in Section Miscellaneous Property in Sec.	T R T R S T R S T R S T R S T R S T R S T R S T R S T R S T R S T S T	e (005)/	Q/ Regist			1293	n		e Ni	umbi	er	
4.	, ,												
5.		Recorded Plat				_			_				
υ.	Filvate Claims				ĵ	Ť	ĬĬ	П	Ť	T	怈	Ì	7
					2 -	6 I	<u> </u>	11		-3	T _i	\top	-1- I
1.	Bryan L. Boss	in a field survey on	APRIL 14, 2000		3 4				\perp	<u></u>		\perp	<u> </u>
dο	hereby certify that under	requirements of P.A. 74, Michiga	an P.A. of 1970, the co	orner points mentione	d 5		Li	Li	\perp	Ľ	Ц		ľ
		re in conformance with regulation			6 -	 - 18	 -17-	1.	,	 -15 —	\perp !	.4	 -131
		nstructions of the United States of a Court of Law and/or that th				Ĩ.	LÏ	ĻΪ	4	Ĩ.	\sqcup	4	-
ab	ove were in conformance	with the rules of the Michigan	Board of Land Surveyo	ors or by a Decree of	а в	. 19	- 20 -	- 21		-22 	-1 -2	3 -	- 24 ·
ΘХ	iurt of Law; established pressed below.	, re-established, monumented,	, re-monumented, re	covered, found as	9	-		+	+	╌	┼╾┤		+
N	TE: Not more than 4	corners, all in the same town	n and range, may be	recorded	10	-30-	- 2 ₉ -		•+	-27	┼┆	6+	-25
	on this certificate	€.			."h	╅╴	╁┼╴	+	十	+	H	+	十
		•			.12	- 3	32-	-3	<u>;</u>	-34-	十章	5+	-36
Α.		I monument and accessories	and/or subsequent r	estoration:	13 🛴					ш.			
	1823 BY S. SIBLEY, DE SET POST W. OAK 6" S 44 1/2 W B. OAK 10" N 25°E 54 I	48 LINKS											
	·•												

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: CORNER B-9 IS LOCATED UNDER A HOUSE. THE LOCATION WAS ESTABLISHED FROM THE PLAT OF "BEN-HUR FARMS NO. 1" LIBER 4 PAGE 3 L.C.R.. REFERENCE POINTS WERE ESTABLISHED AT TWO POINTS:

OOS "NORTH" FOUND 3/4" IRON PIPE NORTH NORTH 30.63" OC. "WEST" FOUND 1/2" ROD N89*50'04"W 132.00 FEET

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

NORTH (005)

SET 1 1/4" X 36" PIPE AND BRASS CAP STAMPED "LIVINGSTON COUNTY REMONUMENTATION

WITNESS"

N 5°E 34.54' SET REMON NAIL/TAG W/SIDE 12"

OAK

EAST 33.57' SET REMON NAIL/TAG N/SIDE 18" OAK SOUTH 9.54' NW CORNER CONCRETE STEPS WEST 9.71' SET REMON NAIL/TAG S/SIDE 18" OAK

WEST (006) SET 1 1/4" X 36" PIPE AND BRASS CAP STAMPED "LIVINGSTON COUNTY REMONUMENTATION

WITNESS'

NORTH 23.00' SET REMON NAIL/TAG E/SIDE 14"

ASPEN

N85°E 8.31' SET REMON NAIL/TAG S/SIDE 10" **ASPEN**

S85°E 4.56' SET REMON NAIL/TAG N/SIDE 10"

ASPEN

N45°W 13.65' SET REMON NAIL/TAG S/SIDE 14" ASPEN

NOVED BY LIVING STOK COUNTY 4-5-2000 CO. REP.

29238

PEER GROUP ON

Date

OF MICHIG BRYAN L B095 and Striveyo NO. 29238 SUR LAND