SURVEY & REMONUMENTATION

Signed by _

Surveyor's Michigan License No.

FEB 2 6 2001		
	CORNER RECORDATION CERTIFICATE	! !! !!!!!! !!
SECTION Filing R	equirement of Act 74, Mich. P.A. 197	U
LIVINGSTON Located in: B	RIGHTON Corner Code #	
(County)	NIGHTON COMBI Code #	2000 OCT 191A 10:31
1. Public Land Survey $\left(\begin{array}{c} T & 2N \\ T & \end{array}\right)$ R	<u>6E</u> <u>E-7</u>	NANCY HAVIL AND REGISTER OF DEEDS
TR		LIVĪNGŠTŌN ČOŬŇŤŸ, MI. 48843
2. Property Controlling S T R in Section S T R		LSC #1298 m
3. Miscellaneous S 21 T 2N R Property in Sec. S 21 T 2N R	GE CO7 / Baris	ster of Deeds Stamp and File Number
4. Lot No , Recorded Plat		_
5. Private Claims		ABCDEFGHIJK
·		2 6 5 4 3 2
		3-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1
, Bryan L. Boss , in a field survey on	MAY 2, 2000	, 4 - 7 8 10 17
do hereby certify that under requirements of P.A. 74, M in lines 1 and 2 above were in conformance with re	ichigan P.A. of 1970, the corner points mention	ed 6
current manual of survey instructions of the United	States Department of the Interior, Bureau of Ler	nd 6 18 17 16 15 14
Management or by a decree of a Court of Law and/or t	hat the corner points mentioned in lines 3,4 and	i5 7├ ─├─}─}─}─}
above were in conformance with the rules of the Mic Court of Law; established, re-established, monume	higan Board of Land Surveyors or by a Decree o	f a 8 19 20 21 22 23 -
expressed below.	ando, re-monamented, recovered, round as	[╵] ╺╏ ╌╏╶╏╶╏┈╏┈╏┈╏┈╏╸╏
NOTE: Not more than 4 corners, all in the same	town and range, may be recorded	10 30 29 28 27 26
on this certificate.		11 12 31 33 34 34
A. Description of original monument and accesso	ories and/or subsequent restoration:	13
1823 BY S. SIBLEY, DEPUTY SURVEYOR	nice and/or subsequent restoration.	
CORNER NOT SET IN LAKE ESTABLISHED 80 CHAINS NORTH OF E-8	·	
• •		
B. Description of corner evidence found and/or n	nethod applied in restoring or reestablishing	corner:
CORNER ESTABLISHED ALONG THE LINE D-7 TO) F-7 N 86°55'06" E	
2663.78 FEET FROM D-7 TWO REFERENCE POINTS WERE ESTABLISHED		•
∞7 POINT "A" LIES N 86°55'06" E 444.31 FROM E-7		
POST POINT "B' LIES S 03*14'51" E, 837.64' FROM E-7	STEP IN LOCATION	
NOTE: THIS CORNER WAS PREVIOUSLY RECOR AT A DIFFERENT LOCATION	(DED IN L.S.C. 1/1/	
•		
 Description of monument for corner and acce 	ssories established to perpetuate locating t	the position of the corner:
REFERENCE POINT "A" (007)	REFERENCE POINT "B" (008)	•
SET 1 1/4' X 36" PIPE AND BRASS CAP STAMPED "LIVINGSTON COUNTY REMONUMENTATION	SET BRASS MONUMENT CAP STAMPED "LIVINGSTON COUNTY REMONUMENTATI	ON
WITNESS"	WITNESS" ON EXISTING CONCRETE MON	
N 31-32-13 E 219.46' CONCRETE MONUMENT N 33-58-57 E 224.86' CONCRETE MONUMENT	WITH 1/2" IRON NORTH 22.95' REMON NAIL/TAG S/SIDE 1/	אַראַ "ייר
N 74-12-35 E 134.39' FOUND 1/2" BOSS IRON	ELDER	
N 39-05-41 E 74.92' SET REMON NAIL/TAG E/SIDE 36" WILLOW	N 90°E 128.03' REMON NAIL/TAG S/SIDE SOUTH 5.31' REMON NAIL/TAG E/SIDE 50'	'WILLOW
S 03-29-43 E 76.29' SET REMON NAIL/TAG N/SIDE	S 40°W 95.76' REMON NAIL/TAG N/SIDE 24	
24" OAK	WILLOW	ANTE OF MICHIGA
S 33-47-39 E 62.21 SET REMON NAIL/TAG N/SIDE 24" OAK		SAILE OF MICHIQUE
S 55-50-45 W 33.40' SET REMON NAIL/TAG E/SIDI	=	BRYAN L.
36" WILLOW WEST +/- 18' TO EDGE OF WATER	· · · · · · · · · · · · · · · · · · ·	* BOSS * Land Surveyor **
		NO.

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, REVISED MAY 14, 19 REVISED JAN., 19

CAND SU

Sept. 7, 2000

Date

29238