

# SURVEY & REMONUMENTATION

FEB 26 2001

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

FILED

### SECTION

For corners in

<u>LIVINGSTON</u> (County)	Located In:	Corner Code #
1. Public Land Survey	<u>T3N R3E</u>	<u>C-03</u>
	T <u>    </u> R <u>    </u>	<u>    </u>
	T <u>    </u> R <u>    </u>	<u>    </u>
	T <u>    </u> R <u>    </u>	<u>    </u>
2. Property Controlling in Section	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>
	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>
3. Miscellaneous Property in Sec.	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>
	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>

2000 OCT 30 1A 9:22

NANCY HAVILAND  
REGISTER OF DEEDS  
LIVINGSTON COUNTY, MI.  
48843

9 LSC #1335 m  
Register of Deeds Stamp & File Number

4. Lot No.         , Recorded Plat                                   
5. Private Claims   

I, JACK K. SMITH, in a field survey on OCTOBER 11, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

1	A	B	C	D	E	F	G	H	I	J	K	L
2		6		5		4		3		2		1
3			7		8		9		10		11	12
4		7		8		9		10		11		12
5												
6		18		17		16		15		14		13
7												
8		19		20		21		22		23		24
9												
10		30		29		28		27		26		25
11												
12		31		32		33		34		35		36
13												

A. Description of original monument and accessories and/or subsequent restoration:

GLO 1825 SYLVESTER SIBLEY SET POST  
TAMARACK 7" N44°E 2.64'  
TAMARACK 8" S20 1/2°W 13.86'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

THE EXISTING CORNER IS A 1/2" REROD APPROXIMATELY 2 FEET WEST OF THE CENTERLINE OF STOW ROAD (GRAVEL). THERE IS A SECOND REROD 3 FEET EASTERLY. THERE IS A FENCE LINE TO THE EAST AND SWAMP TO THE WEST. THE WESTERLY REROD APPEARS TO BE THE ONLY POSITION USED SINCE 1980 AND WAS PROBABLY USED IN 1931 BY CLAY GORDON.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-03 NORTHWEST CORNER SECTION 8, T3N, R3E, HANDY TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN:  
SET 1 1/4" x 36" STEEL PIPE WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP STAMPED SURVEYOR #35999 IN PLACE OF THE WESTERLY 1/2" REROD.

N80°E	SPIKE AND LIV. CO. REMON TAG IN NORTH SIDE OF 40" MULTI-WILLOWS	37.10'
S80°E	SPIKE AND LIV. CO. REMON TAG IN SOUTH SIDE OF UTILITY POLE	36.12'
S65°E	CENTER OF 2" PINE	57.36'
S40°E	CENTER OF 3" PINE	133.82'
S85°W	SPIKE AND LIV. CO. REMON TAG IN NORTH SIDE OF UTILITY POLE	81.68'
E°LY	3.5'± TO CENTER LINE OF ROAD & 1/2" IRON ROD	



Signed by Jack K. Smith Date 10-16-2000

Surveyor's Michigan License No. 35999