

SURVEY &
REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in

LIVINGSTON Located In: Corner Code #
(County)
1. Public Land Survey T 3 N R 3 E D-05
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

2000 OCT 30 A 9:22

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

LSC #1339m

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, JACK K. SMITH, in a field survey on OCTOBER 11, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

1	A	B	C	D	E	F	G	H	I	J	K	L
2		6		5		4		3		2		1
3												
4		7		8		9		10		11		12
5												
6		18		17		16		15		14		13
7												
8		19		20		21		22		23		24
9												
10		30		29		28		27		26		25
11												
12		31		32		33		34		35		36
13												

A. Description of original monument and accessories and/or subsequent restoration:

GLO 1825 SYLVESTER SIBLEY SET POST
TAMARAC 10" S87°E 26.4'
BLACK ASH 8" N80°W 117.48'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

THE EXISTING CORNER IS A 1 1/4" ID PIPE SEVERLY TIPPED TO THE NORTHEAST IN THE RAILROAD BED STONE 8' NORTHERLY OF THE CENTERLINE OF THE ROAD.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-05 SOUTH 1/4 CORNER SECTION 8, T3N, R3E, HANDY TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN;
SET 1 1/4" x 36" STEEL PIPE WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP STAMPED SURVEYOR #35999 IN PLACE OF THE 1 1/4" PIPE THAT CURRENTLY MARKS THE CORNER.

NORTH 1/2" STEEL REROD WITH DESINE CAP 42.15'
SOUTH CENTER LINE OF NORTH RAIL OF RAILROAD TRACKS 4.68'
EAST S.W. CORNER OF ELECTRIC SWITCH BOX 131.70'
N88°W SOUTH CORNER OF RAILROAD MILE POST (DET 65) 180.63'
N70°E SPIKE AND LIV. CO. REMON TAG IN SOUTH SIDE OF UTILITY POLE 39.97'

Signed by [Signature] Date 10-16-2000

Surveyor's Michigan License No. 35999

