

SURVEY & REMONUMENTATION

FEB 25 1999

FILED

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

LIVINGSTON

(County)

Located In:

Corner Code #

1. Public Land Survey

T 3N R 4E

F7

2. Property Controlling
in Section

S

T

R

3. Miscellaneous
Property in Sec.

S

T

R

4. Lot No. , Recorded Plat

5. Private Claims

1998 AUG 20 P 4: 42

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

L.S.C. #854m

Register of Deeds Stamp & File Number

I, CHARLES E GARLOCK, in a field survey on AUG. 5, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO SURVEY DATED: APRIL 15, 1825 BY S SIBLEY, DS
GLO WITNESSES: WO 32-S19'E-28 LKS
HICK 7-N14½W-39 LKS.

ADDITIONAL DATA ON REAR OF SHEET

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2" I. ROD IN CENTERLINE OF "T" ROAD INTERSECTION AND LINES WITH FENCE LINE TO THE SOUTH. ALSO FOUND 1/2" I. ROD NNW 11' OF THE ABOVE IRON, NO KNOWN WITNESSES TO THIS POINT OR WHO HAS USED IT IN THE PAST, ALL SURVEYS APPEAR TO GO TO THE FIRST IRON FOUND.

NNE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F7: N¼ COR. SEC. 21, T3N-R4E, HOWELL TWP., LIV. CO. MI, RESET 1/2" I. ROD WITH 1¼" X 36" BREAKAWAY I. PIPE WITH LIV. CO. REMON BRASS CAP ON TOP.
S1E-27.14'-SP & TAG E/S 22" HICKORY
S71W-58.32'-SP & TAG N/S 16" HICKORY
N25W-84.08'-SP & TAG E/S U. POLE
N49W-52.48'-SP & TAG S/S 26" HICKORY
(N29E - 11.60' - 1/2" IRON ROD)

Signed by

Charles E. Garlock

Date AUGUST 8, 1998

Surveyor's Michigan License No. 14762

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY

PEER GROUP ON 3/4/98 CO. REP JED

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983
REVISED OCT., 1995

1	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

