

CORNER SUMMARY

1-9: NORTHWEST CORNER SECTION 26, T3N-R4E, HOWELL TOWNSHIP,
LIVINGSTON COUNTY, MICHIGAN.

GLO SURVEY DATED APRIL 15, 1825 BY S SIBLEY, DS, AND NONE OF THE
GLO WITNESSES REMAIN.

EARLIEST KNOWN ACTIVITY WAS IN 1933 BY AN UNKNOWN SURVEYOR, TO A
STONE, AND ONE OF HIS WITNESSES REMAINED IN 1968, 1973 AND 1976.
SINCE 1968 WITNESSES BY C WILSON, P BENTON, CHMP, BOSS, DESINE AND
MYSELF ARE PRETTY MUCH THE SAME AND TO THE SAME POINTS AND CHECK
TODAY. A 1/2" I. ROD WAS FOUND IN LINE WITH A FENCE LINE TO THE
WEST AND ON THE CENTERLINE OF ROADS NORTH, EAST AND SOUTH.
MEASURES TO THE NORTH ARE 2661.14 AND 2661.10 BY MYSELF, 2660.79
AND 2660.99 BY CHMP, 2660.99 BY BOSS AND 2662.06 BY BENTON;
MEASURES EAST ARE 2653.92 BY DESINE, 2653.88 BY CHMP AND BOSS AND
2653.93 BY MYSELF; MEASURES SOUTH 2658.79 BY DESINE, 2659.20 BY
WASHTENAW ENGR AND 2658.77 BY BOSS AND MEASURES WEST ARE 2644.46
BY MYSELF AND 2648.45 BY BENTON. ONE ACT 74 IS RECORDED AND NINE
ACT 132'S. CORNER IS LOCATED IN A GRAVEL ROAD AND IS SUITABLE FOR
GPS.



CHARLES E GARLOCK
PS14762
HOW9619

3N4E 27

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Livingston

(County)

Located In:

Corner Code 1-10

1. Public Land Survey

T 3N R 4E

1-10

T _____ R _____

T _____ R _____

T _____ R _____

2. Property Controlling
in Section

S _____ T _____ R _____

S _____ T _____ R _____

3. Miscellaneous
Property in Sec.

S _____ T _____ R _____

S _____ T _____ R _____

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

FILED
MAY 30 3 46 PM '96
NANCY HAYLAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI
48843

L.S.C. #533m

Register of Deeds Stamp & File Number

Charles E Garlock, in a field survey on May 22, 19 96,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
GLO survey dated:.....April 15, 1825 by S Sibley DS
GLO witnesses:.....Tam 4- N85E-33 lks
Tam 5-N81W- 9 lks

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

SURVEY &
REMONUMENTATION

AUG 06 1996

COMMISSION

Additional historical survey data on rear of sheet.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
Found 1/2" I. Rod on centerline of Brewer Rd. to the North



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
I-10: W 1/4 cor. Sec. 26 T3N-R4E, Howell Twp. Liv. Co. MI. set 1 1/4" X 36" breakaway I. Pipe
with Liv. Co. Remon brass cap on top at -0.6' in gravel road.
N23E-78.25'-sp & tag W/s U Pole
S68E-39.49'-sp & tag S/s of Light Pole
S22E-104.42'-sp & tag E/s of Light Pole
S58W-30.07'-ctr. 2" steel post, Brewer road sign post/
S6E-55.81'-constr. centerline M-59

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 3-6-96 CO. REP JED

Signed by Charles E Garlock Date May 23, 1996

Surveyor's Michigan License No. 14762