

# SURVEY & REMONUMENTATION

FEB 26 2001

## SECTION

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in

<u>LIVINGSTON</u>	Located in:	Corner Code #
(County)		
1. Public Land Survey	T <u>3</u> N R <u>4</u> E	<u>B-07</u>
	T <u>   </u> R <u>   </u>	<u>          </u>
	T <u>   </u> R <u>   </u>	<u>          </u>
	T <u>   </u> R <u>   </u>	<u>          </u>
2. Property Controlling	S <u>   </u> T <u>   </u> R <u>   </u>	<u>          </u>
in Section	S <u>   </u> T <u>   </u> R <u>   </u>	<u>          </u>
3. Miscellaneous	S <u>   </u> T <u>   </u> R <u>   </u>	<u>          </u>
Property in Sec.	S <u>   </u> T <u>   </u> R <u>   </u>	<u>          </u>

2000 AUG 29 1 A 9 28

NANCY HAVILAND  
REGISTER OF DEEDS  
LIVINGSTON COUNTY, MI.  
48843

q' LSC #1237m  
Register of Deeds Stamp & File Number

4. Lot No.           , Recorded Plat             
5. Private Claims           

I, CHARLES E. GARLOCK, in a field survey on JULY 13, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5			4		3		2		1
3													
4		7		8			9		10		11		12
5													
6		18		17			16		15		14		13
7													
8		19		20			21		22		23		24
9													
10		30		29			28		27		26		25
11													
12		31		32			33		34		35		36
13													

### A. Description of original monument and accessories and/or subsequent restoration:

GLO 1825 S. SIBLEY SET POST  
WHITE ASH 14" N27°W 4.62'  
WHITE OAK 10" S80 1/2°E 18.48'

### B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND A 1/2" IRON ROD ON THE CENTER LINE OF WARNER ROAD (EAST AND WEST) WITH FENCE LINE TO THE NORTH AND NO OCCUPATION TO THE SOUTH.

### C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:


B-07 NORTH 1/4 CORNER SECTION 19, T3N, R4E, HOWELL TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN:  
SET 1 1/4" X 36" BREAKAWAY STEEL PIPE WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP STAMPED WIT  
SURVEYOR #14762 WHERE 1/2" IRON ROD WAS FOUND.

N5°E SP&TAG W/S 16" HICKORY  
N40°E SW CORNER HOUSE FOUNDATION #5490  
S65°E SP&TAG N/S 40" OAK  
S65°W SP&TAG N/S 30" HICKORY  
SOUTH 2' +/- CENTERLINE OF E-W ROAD

34.85'  
81.17'  
87.54'  
73.70'

Signed by Charles E. Garlock Date 7-22-00

Surveyor's Michigan License No. 14762



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28,  
REVISED MAY 14/95 REVISED JAN. 1983 REVISED OCT., 1995

PA. 315 1002, APPROVED BY LIVINGSTON COUNTY  
FIRM GROUP ON 3-15-2000, CO. REP. JED