

SURVEY & REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

LIVINGSTON
(County)

Located In:

Corner Code #

1. Public Land Survey

T3N R4E C-07

2. Property Controlling in Section

S T R

3. Miscellaneous Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

2000 AUG 29 A 9 28

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

LSC #1239m
Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2	6		5			4		3		2		1
3												
4	7		8			9		10		11		12
5												
6	18		17			16		15		14		13
7												
8	19		20			21		22		23		24
9												
10	30		29			28		27		26		25
11												
12	31		32			33		34		35		36
13												

I, CHARLES E. GARLOCK, in a field survey on JULY 13, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO 1825 S. SIBLEY SET POST
BEECH 7" N39 1/2°E 12.54'
IRONWOOD 5" S37 1/2°W 7.92'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND A RAILROAD SPIKE ABOUT 1 FOOT SOUTH OF THE NORTH EDGE OF GRAND RIVER PAVEMENT IN LINE WITH THE CENTERLINES OF THE ROADS TO THE NORTH, EAST AND WEST. THE CENTERLINE OF THE ROAD TO THE SOUTH WAS ABOUT 5 FOOT TO THE WEST.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-07 NORTHEAST CORNER SECTION 19, T3N, R4E, HOWELL TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN:
SET 1 1/4" X 36" BREAKAWAY STEEL PIPE WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP STAMPED WITH SURVEYOR #14762 WHERE THE RAILROAD SPIKE WAS FOUND AND SET MONUMENT BOX.

S20°W SP&TAG W/S UTILITY POLE
N76°W SP&TAG S/S UTILITY POLE
N23°W SE CORNER OF BUILDING
N26°E SP&TAG W/S 10" PINE

72.90'
144.59'
75.78'
96.59'


Signed by

Charles E. Garlock

Date

7-22-00

Surveyor's Michigan License No. 14762



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN. 1983
REVISED OCT. 1995

P.A. 345 1980, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 3-15-2000 CO. REP JEO