

SURVEY & REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in

LIVINGSTON
(County)

Located In:

Corner Code #

1. Public Land Survey

T3N R4E

C-08

T R

T R

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

2000 AUG 29 1 A 9 29

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

LSC #1240m

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, CHARLES E. GARLOCK, in a field survey on JULY 13, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2		6		5		4		3		2		1
3												
4		7		8		9		10		11		12
5												
6		18		17		16		15		14		13
7												
8		19		20		21		22		23		24
9												
10		30		29		28		27		26		25
11												
12		31		32		33		34		35		36
13												

A. Description of original monument and accessories and/or subsequent restoration:

GLO 1825 S. SIBLEY SET POST
DOUBLE LYNNWOOD 30" S60°E 34.32'
WHITE OAK 28" S71 1/2°W 20.46'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:


FOUND 1/2" IRON ROD ON THE CENTERLINE OF THE ROAD TO THE NORTH AND ABOUT 5' NORTH OF THE ROADS TO THE EAST AND WEST. THE FOUND IRON IS IN LINE WITH A FENCE LINE TO THE SOUTH.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-08 EAST 1/4 CORNER SECTION 19, T3N, R4E, HOWELL TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN:
SET 1 1/4" X 36" BREAKAWAY STEEL PIPE WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP STAMPED WITH SURVEYOR #14762 WHERE OLD 1/2" IRON ROD WAS FOUND.

ON CENTERLINE OF ROAD NORTH
N20°E SP&TAG W/S 36" COTTONWOOD
N15°W SP&TAG E/S FORKED 24" ELM
S75°E SP&TAG SW/S UTILITY POLE
SOUTH SP&TAG E/S WOOD POST
S80°W SP&TAG N/S UTILITY POLE

61.93'
148.92'
75.32'
45.81'
139.82'



Signed by

Charles E. Garlock

Date

7-22-00

Surveyor's Michigan License No. 14762

PA. 345 1980, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 3-15-2000 CO. REP JED

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 19
REVISED MAY 14, 1975
REVISED JAN, 1983
REVISED OCT, 1995