

SURVEY & REMONUMENTATION

FEB 26 2001

FILED

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

2000 AUG 29 A 9:29

LIVINGSTON Located In: Corner Code #
(County)
1. Public Land Survey T3N R4E C-09
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

LSC #1241 m
Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, CHARLES E. GARLOCK, in a field survey on JULY 13, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2	6		5			4		3		2		1
3												
4	7		8			9		10		11		12
5												
6	18		17			16		15		14		13
7												
8	19		20			21		22		23		24
9												
10	30		29			28		27		26		25
11												
12	31		32			33		34		35		36
13												

A. Description of original monument and accessories and/or subsequent restoration:

GLO 1825 S. SIBLEY SET POST
TAMARACK 10" S11 1/2° W 160.38'
TAMARACK 11" N40 1/2°E 143.22'
IN SWAMP

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2" IRON ROD ON TOP OF A MOUND OF DIRT 20 FEET IN DIAMETER AND ABOUT 4 FEET HIGH WITH OLD FENCE LINES TO THE NORTH, SOUTH AND EAST. THERE IS OPEN FIELD FOR APPROXIMATELY 600' TO THE WEST THEN A FENCE LINE.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-09 SOUTHEAST CORNER SECTION 19, T3N, R4E, HOWELL TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN:
SET 1 1/4" X 36" STEEL PIPE WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP STAMPED WITH SURVEYOR #14762 WHERE OLD 1/2" IRON ROD WAS FOUND.

S40°E SP&TAG SW/S 16" ELM 6.64'
N15°W SP&TAG E/S 12" WILLOW 30.70'
S35°W SP&TAG W/S 5" POPLAR 20.15'
SOUTH SP&TAG W/S 8" POPLAR 49.82'

Signed by Charles E. Garlock Date 7-22-00

Surveyor's Michigan License No. 14762



PA. 345 1990, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 3-15-2000 CO. REP JED

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1983
REVISED MAY 14, 1975
REVISED JAN., 1983
REVISED OCT., 1995