

SURVEY & REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in

LIVINGSTON Located In: Corner Code #
(County)
1. Public Land Survey T3N R4E D-07
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

2000 AUG 29 1A 9 29

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

LSC #1243m
Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, CHARLES E. GARLOCK, in a field survey on JULY 13, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L
1												
2	6		5			4		3		2		1
3												
4	7		8			9		10		11		12
5												
6	18		17			16		15		14		13
7												
8	19		20			21		22		23		24
9												
10	30		29			28		27		26		25
11												
12	31		32			33		34		35		36
13												

A. Description of original monument and accessories and/or subsequent restoration:

GLO 1825 S. SIBLEY SET POST
BLACK OAK 16" S26° E 50.16'
BLACK OAK 22" N6°W 17.16'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2" IRON ROD ON THE CENTERLINE OF WARNER ROAD AND A WIDE HEDGEROW TO THE SOUTH. OLD FENCE REMAINS TO THE SOUTH ARE WITHIN 3+/- FEET OF BEING IN LINE WITH IRON. DISTANCE TO THE WEST VARY BY 0.04' AND VARY TO SOUTH BY 0.65'.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-07 NORTH 1/4 CORNER SECTION 20, T3N, R4E, HOWELL TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN:
SET 1 1/4" X 36" BREAKAWAY STEEL PIPE WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP STAMPED WITH SURVEYOR #14762 WHERE OLD 1/2" IRON ROD WAS FOUND.

N3°W SP&TAG W/S 20" HICKORY
S3°W SP&TAG E/S 16" CHERRY
S40°E SP&TAG SW/S 8" ELM
S75°E SP&TAG N/S 18" WALNUT
1' +/- SOUTH OF CENTERLINE OF E-W ROAD

14.68'
38.08'
38.81'
75.50'



Signed by Charles E. Garlock

Date 7-22-00

Surveyor's Michigan License No. 14762

PA. 345 1980, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 4-5-2000 CO. REP JED

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14/95 REVISED JAN. 1983
REVISED OCT., 1995