

SURVEY & REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in

LIVINGSTON Located In: Corner Code #
(County)
1. Public Land Survey T3N R5E C-12
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

2000 AUG 29 A 9:30

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
46843

LSC #1258m

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, CHARLES E. GARLOCK, in a field survey on JULY 10, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

1	A	B	C	D	E	F	G	H	I	J	K	L
2		6		5		4		3		2		1
3												
4		7		8		9		10		11		12
5												
6		18		17		16		15		14		13
7												
8		19		20		21		22		23		24
9												
10		30		29		28		27		26		25
11												
12		31		32		33		34		35		36
13												

A. Description of original monument and accessories and/or subsequent restoration:

GLO 1823 S. SIBLEY SET POST
WHITE OAK 16" WEST 46.2'
WHITE OAK 8" S 81° E 24.42'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2" IRON ROD IN A MONUMENT BOX APPROXIMATELY 3' EAST OF THE NORTH-SOUTH CENTERLINE OF EAGER ROAD IN LINE WITH THE NORTH PROPERTY LINE OF THE CHEMUNG HILLS GOLF COURSE AND AN OCCUPATION LINE TO THE WEST.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:


C-12 WEST 1/4 CORNER SECTION 32, T3N, R5E, OCBOLA TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN:
SET 1 1/4" X 36" BREAKAWAY STEEL PIPE WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP STAMPED WITH SURVEYOR #14762 IN PLACE OF THE 1/2" IRON ROD IN THE MONUMENT BOX.

S40°W SP&TAG E/S 9" OAK
WEST SP&TAG S/S 16" OAK
N20°E SP&TAG W/S 12" OAK
EAST BACK OF CONCRETE CURB
WEST CENTERLINE OF ASPHALT ROAD N&S

109.30'
33.00'
111.90'
12.71'
3.5' +/-

Signed by Charles E. Garlock Date 7-21-00

Surveyor's Michigan License No. 14762



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 24, 1983
REVISED MAY 14, 1975 REVISED JAN., 1983 REVISED OCT., 1995

P.A. 345 1980, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 3-01-2010 CO. REP JED