

SURVEY & REMONUMENTATION

FEB 26 2001

FILED

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

LIVINGSTON Located In: _____ Corner Code # _____
(County)
1. Public Land Survey T 3 N R 6 E J-03
T _____ R _____
T _____ R _____
T _____ R _____
2. Property Controlling S _____ T _____ R _____
in Section S _____ T _____ R _____
3. Miscellaneous S _____ T _____ R _____
Property in Sec. S _____ T _____ R _____

2000 AUG 29 A 9:29

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

LSC #1250m

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, CHARLES E. GARLOCK, in a field survey on JULY 11, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3			2		1	
3										⊙			
4	7		8		9		10			11		12	
5													
6	18		17		16		15			14		13	
7													
8	19		20		21		22			23		24	
9													
10	30		29		28		27			26		25	
11													
12	31		32		33		34			35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

GLO 1823 S. SIBLEY SET POST
WHITE OAK 14" S37°W 27.72'
WHITE OAK 12" N14°W 64.02'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:


WE FOUND AN IRON ROD 4 FEET SOUTH OF THE CENTERLINE OF AN EAST-WEST ROAD AND WITH HEDGE ROW TO THE NORTH AND SOUTH.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-03 NORTH 1/4 CORNER SECTION 11, T3N, R6E, HARTLAND TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN:
SET 1 1/4" X 36" BREAKAWAY STEEL PIPE WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP STAMPED WITH SURVEYOR #14762 IN THE PLACE OF THE IRON ROD.

S50°W SP&TAG N/S 15" OAK 37.26'
S75°W SP&TAG N/S UTILITY POLE 80.27'
NORTH SP&TAG W/S 18" OAK 51.21'
N35°W SP&TAG E/S 16" OAK 39.63'
NORTH 4' +/- CENTERLINE OF CLYDE ROAD

37.26'
80.27'
51.21'
39.63'



Signed by Charles E. Garlock Date 7-21-00

Surveyor's Michigan License No. 14762