

# SURVEY & REMONUMENTATION

FEB 26 2001

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in SECTION

LIVINGSTON Located in: Corner Code #  
(County)  
1. Public Land Survey T3N R6E K-03  
T R  
T R  
T R  
2. Property Controlling S T R  
in Section S T R  
3. Miscellaneous S T R  
Property in Sec. S T R

FILED

2000 AUG 29 1 A 9:30

NANCY HAVILAND  
REGISTER OF DEEDS  
LIVINGSTON COUNTY, MI.  
48843

LSC #1252m  
Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, CHARLES E. GARLOCK, in a field survey on JULY 11, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

1	A	B	C	D	E	F	G	H	I	J	K	L
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

A. Description of original monument and accessories and/or subsequent restoration:

GLO 1823 S. SIBLEY SET POST  
BLACK OAK 12" N76°W 245.52'  
BLACK OAK 8" EAST 249.48'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

WE FOUND A RAILROAD SPIKE ON THE CENTERLINE OF FENTON AND CLYDE ROAD INTERSECTION.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-03 NORTHEAST CORNER SECTION 11, T3N, R6E, HARTLAND TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN:  
SET 1 1/4" X 30" STEEL PIPE (ON TOP OF LARGE STONE) WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP  
STAMPED WITH SURVEYOR #14762 IN THE PLACE OF THE RAILROAD SPIKE AND IN A SET MONUMENT BOX.

S75°E SP&TAG N/S 15" OAK  
N75°E SP&TAG S/S FORKED 16" LOCUST  
N40°E SP&TAG N/S 24" WILLOW  
S50°W SP&TAG N/S UTILITY POLE  
ON CENTERLINE OF CLYDE ROAD  
1' +/- WEST OF CENTERLINE OF FENTON ROAD

185.44'  
142.15'  
113.20'  
57.55'


Signed by

*Charles E. Garlock*

Date

7-21-00

Surveyor's Michigan License No. 14762



FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1978  
REVISED JAN., 1982  
REVISED OCT., 1995

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY

PFEP GROUP ON 2-16-2000 CO. REP JED