

SURVEY & REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in

LIVINGSTON Located In: Corner Code #
(County)
1. Public Land Survey T3N R6E L-03
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

2000 AUG 29 1 A 9 30

NANCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
46843

LSC #1254m

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, CHARLES E. GARLOCK, in a field survey on JULY 11, 2000 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

GLO 1823 S. SIBLEY SET POST
WHITE OAK 25" N43°E 17.16'
WHITE OAK 10" S35°W 33.00'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:


WE FOUND TWO IRONS IN THE CENTER LINE OF CLYDE ROAD (GRAVEL) THAT ARE IN LINE WITH WIDE HEDGE ROWS TO THE NORTH AND SOUTH. THE WEST IRON WAS A 1/2" IRON PIPE AND THE EAST IRON WAS A 1/2" IRON ROD. THE WEST IRON FITS BETTER WITH DISTANCES USED IN THE PAST.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-03 SOUTH 1/4 CORNER SECTION 1, T3N, R6E, HARTLAND TOWNSHIP, LIVINGSTON COUNTY, MICHIGAN:
SET 1 1/4" X 36" BREAKAWAY STEEL PIPE WITH LIVINGSTON COUNTY REMONUMENTATION BRASS CAP STAMPED WITH SURVEYOR #14762 IN THE PLACE OF THE WEST IRON.

EASTERLY 3/8" IRON ROD
NORTH SP&TAG W/S 24" WALNUT
N75°W SP&TAG S/S CUT OFF UTILITY POLE (NEXT TO T. PEDESTAL)
N75°E SP&TAG S/S 12" HICKORY
S80°E SP&TAG N/S 15" ELM

4.60'
57.18'
79.89'
92.93'
57.30'



Signed by

Charles E. Garlock

Date

7-21-00

Surveyor's Michigan License No. 14762

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY

PEER GROUP ON 3-1-2000 CO. REP JED

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 19
REVISED MAY 14, 1975
REVISED JAN. 1985
REVISED OCT. 1996