

LIVINGSTON

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—	LOCATED IN—	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY— 24 T. 4 N. 4 E.		K-9, L-9
2. PROPERTY CONTROLLING IN SECTION—, T. N. S., R. E. W.		
3. MISCELLANEOUS PROPERTY IN SECTION—, T. N. S., R. E. W.		
4. LOT NO.—, RECORDED PLAT—		
5. PRIVATE CLAIMS—		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Donald Bissell, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on November, 1981, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

K-9 Set 4"x 36" concrete monument with aluminum cap on N-S fence and on line between south one quarter of Section 24 and south one quarter of Section 23. Set cedar post beside concrete monument.	L-9 Set 4"x 36" concrete monument with aluminum cap on line from S.E. corner, Section 24, through 1/8 corner at half the distance from S.E. corner, Section 24
--	--

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-9 North 115', North edge of marsh West, 33.6', 1/2" iron rod with plastic cap.	L-9 4"x 36" concrete monument with aluminum cap. N 34° W, 8.30', 8" Cherry, Spike and Tag N 23° W, 12.87', 6" Cherry, Spike and Tag S 83° E, 117.40', Clump of four 18" Soft Maples, Spike and Tag 6' East of $\frac{1}{2}$ Road to the North 16' South of $\frac{1}{2}$ Road to the East
--	--

SIGNED BY Donald Bissell DATE 12-14-81

SURVEYOR'S MICHIGAN REGISTRATION NO. 18655

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____