SURVEY &

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

FILED

•	1			ZÜÜ	W OCT	30 A	4 9: 2
For corners in				r	HANCY	HAVIL	AND
<u>Livingston</u> Located In: Corner Co (County) Cohoctah Twp.	de			ΓΊΥ	111021	N COUI 8843	ity. Mi.
1. Public Land Survey (T4N R4E 1-7) T R T R	O\ CRegisto	C #132 er of Dec	28 m eds Star	mp&Fi	ile Num	ber	
2. Property Controlling S T R R IN Section S T R R R R R R R R R R R R R R R R R R	/	ΑВ	C D	E F (Э Н 1	. J K	L M
4. Lot No, Recorded Plat			5	1	3	2	1
5. Private Claims		1 ~					
I John H Rauser PS in a field survey on July 17	2000		8	9	10	11.	12
I, John H, Rauser, P.S., in a field survey on July 17 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1 in lines 1 and 2 above were in conformance with regulations and rul current manual of survey instructions of the United States Department	les therefore as required in the 6	l 18	17	16	15	14	13
Management or by a decree of a Court of Law and/or that the corner pol above were in conformance with the rules of the Michigan Board of La Court of Law: established, re-established, monumented, re-monumented, re-mon	ints mentioned in lines 3, 4, and 5,	19	20	21	22	23	24
expressed below:	1	30	29	28	27	26	25
NOTE: Not more than 4 corners, all in the same town and ra on this certificate.	inge, may be recorded 1:	2 31	32	33	34	35	36
(Continued on Back) B. Description of corner evidence found and/or metil Common Section Corner, Sections 14, 15, 22, & 23, Co Found no evidence of original government corner. Corn "witness corner to inaccessible Northwest corner, Sec. 2 the found reference Iron 48,22 feet, using the 19991 sur calculated position of the corner with measurements fror available evidence of the position of the original governm brass cap be placed over the found ½" rerod witness co calculated corner position on line with J-7.	S56W 24.5 lks 20" Whod applied in restoring or hoctah Township, Livingston Cer falls in river. Found ½" rero 23". Calculated a position of throey. Found no conflicting evid in 1973. We recommend that the ment corner and that a standar	reesta county d from 19 c corner ence in the calcul	973 reco by extent he vicin lated po ton Cou	ord, which nding a ity of thit sition be inty with	ch was line from s corne e accep less mo	n I-8 thi r. Verifi ted as t nument	ough ed the he best
 C. Description of monument for corner and accesso corner: 	ries established to perpet	uate lo	cating	the po	sition	of the	
I-7 Common Section Corner, Sections 14, 15, 22, & 23, Co Corner not set. South 48.22' Set standard Livingston County Remo East 58.78' Set standard Livingston County Remo	onumentation Witness monume	ent with b					
South Witness Post / co) N10E	e (R=4.46') tree (R=22.63')						
East Witness Post (OO'Z) \$15W 112.44' Set ½" rod with Rowe Trav. Cap \$50W 75.85' Livingston County Remonumentation Witness North 1.0' Set Carsonite Survey Marker post \$45E 15.06' Set nail with Livingston County Survey Witness N10W 14.55' Set nail with Livingston County Survey Witness N85E 24.26' Set nail with Livingston County Survey Witness	s tag in South face of 6" Box El s tag in East face of 6" Box Eld	der	3		OHN NAME OF STREET OF STRE	R NAL	FYOR A

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY PEER GROUP ON 6.21-2000 CO. REP JCD

alu

Signed by / / / / / Surveyor's Michigan License No. 39096

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS; JAN. 21, 1971
TON COUNTY

ADAPTED FOR WORD PROCESSING MARCH, 1995