SURVEY & REMONUMENTATION

FEB 26 2001

FILED

LAND	CORNER	RECORDATION	CERTIFICATE
	OCIVILIA	1/2001/01/11/014	OF

SECTION

Filing Requirement of Act 74, Mich. P.A. 1970

2000 OCT 30 A 9: 2

Livingston Located In: Corner Code (County) Cohoctah Twp.				R LIV	HANCY EGISTE INGSTO 4	HAYIL R OF UN N COUN 8843	AND EEDS ITY, MI
1. Public Land Survey	LS Registe	C #132 r of Dee		np & Fi	ile Num	ber	
2. Property Controlling S T R In Section S T R 3. Miscellaneous S 22 T 4N R 4E CO2 Property in Sec. S 23 T 4N R 4E CO2	1	А В (C D	E F (э н <u>і</u>	ı J K	L M
4. Lot No, Recorded Plat	- 2 - 3	6	5	4	3	2	1
1, John H. Rauser, P.S. , in a field survey on July 17 2000	4	7	8	9	10	11	12
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the conterpoints mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the 6 current manual of survey instructions of the United States Department of the Interior, Bureau of Land 7				16	15	14	13
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a 8 Court of Law; established, re-established, monumented, re-monumented, recovered, found as a			20	21	22	23	24
expressed below:	10	1 "	29	28	27	26	25
NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.	ed 11 12 13	31	32	33	34	35	36

Description of original monument and accessories and/or subsequent restoration:

1-7 Common Section Corner, Sections 14, 15, 22, & 23, Cohoctah Township, Livingston County In 1823, a wood post was placed in the South side of a stream 25 links (16.5') wide by Sylvester Sibley, Deputy Surveyor. Said

38.5 lks 18" Elm stream runs SE'ly. Two trees were marked at this time: S24E

24.5 lks 20" W. Ash S56W

(Continued on Back)

Description of corner evidence found and/or method applied in restoring or reestablishing corner: В. 1-7

Common Section Corner, Sections 14, 15, 22, & 23, Cohoctah Township, Livingston County
Found no evidence of original government corner. Corner falls in river. Found ½" rerod from 1973 record, which was called a "witness corner to inaccessible Northwest corner, Sec. 23". Calculated a position of the corner by extending a line from I-8 through the found reference Iron 48.22 feet, using the 19991 survey. Found no conflicting evidence in the vicinity of this corner. Verified the calculated postion of the corner with measurements from 1973. We recommend that the calculated position be accepted as the best available evidence of the position of the original government corner and that a standard Livingston County witness monument with brass cap be placed over the found 1/2" rerod witness corner, and one additional witness corner be set East 58.78' from the calculated corner position on line with J-7.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Common Section Corner, Sections 14, 15, 22, & 23, Cohoctah Township, Livingston County 1-7

Comer not set

48.22 South Set standard Livingston County Remonumentation Witness monument with brass cap stamped "39096".

East 58.78 Set standard Livingston County Remonumentation Witness monument with brass cap stamped "39096".

South Witness Post (col)

N10E 4.46' Found nail with tag in West face of 12" Thornapple (R=4.46') S30E 22.62

Found nail with tag in North face of 30" Willow tree (R=22.63')

Found nail with tag in South face of 8" twin Box Elder (R=42.61') West 42.61

East 1.05 Set Carsonite Marker Post

67.85 1/2" re-rod with Rowe Trav. Cap S26E

East Witness Post (002) S15W 112.44' Set '/' rod with Rowe Trav. Cap

Livingston County Remonumentation Witness monument with brass cap stamped "39096" S50W 75.85

North 1.0 Set Carsonite Survey Marker post

15.06 Set nail with Livingston County Survey Witness tag in South face of 6" Box Elder \$45E N10W 14.55 Set nail with Livingston County Survey Witness tag in East face of 6" Box Elder

Set nail with Livingaron County Survey Witness tag in North face of 14" Ash N85E 24.26

arr Signed by Surveyor's Michigan License No. 39096

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SUR P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY

PEER GROUP ON 6.21.2000 CO. REP

REVISED JAN., 1943 ADAPTED FOR WORD PROCESSING MARCH, 1995

MICH

JOHN H

RAUSER

PROFESSIONAL

SURVEYOR

No.