## SURVEY & REMONUMENTATION

FEB 2 6 2001

FILED

SECTION

#### LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

2000 OCT 30 1 A 9: 21

| For corners in  Livingston Located In: Corner Code  |                       |          | RE       | ANCY I<br>MISTER<br>IGSTON<br>48 | OF DEL | EDS     |      |
|---|-----------------------|----------|----------|----------------------------------|--------|---------|------|
| (County) Cohoctah Twp.  1. Public Land Survey T4N R4E 1-8  T R  T R  T R  | Registe               | r of Dee |          | #1329<br>mp & Fi                 |        | iber    | 1    |
| T R T R T R T R T R T R T R T R T R T R   | 1                     | A_B_     | C D      | E F (                            | Э н !  | ΙΊΚ     | L N  |
| 4. Lot No, Recorded Plat  | 2<br>3                | 6        | 5        | 4                                | 3      | 2       | 1    |
|   | 2000                  | 7        | 8        | 9                                | 10     | 11      | 12   |
| do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner polin lines 1 and 2 above were in conformance with regulations and rules therefore as recurrent manual of survey instructions of the United States Department of the Interior, Bu | equired in the 6      | 18       | 17       | 16                               | 15     | 14      | 13   |
| Management or by a decree of a Court of Law and/or that the corner points mentioned in lin above were in conformance with the rules of the Michigan Board of Land Surveyors or by Court of Law; established, re-established, monumented, re-monumented, recovere          | a Decree of a 8       | 19       | 20       | 21                               | 22     | 23      | 24   |
| expressed below:  | 10                    | 1 00     | 29       | 28                               | 27     | 26      | 25   |
| NOTE: Not more than 4 corners, all in the same town and range, may be recon this certificate.   | corded 11<br>12<br>13 | 31       | 32       | 33                               | 34     | 35      | 36   |
| A. Description of original monument and accessories and/or subset Common 1/4 Corner, Sections 22 & 23, T4N-R4E, Cohoctah Township, L In 1823, a wood post was placed by Sylvester Sibley, Deputy Sur  | _ivingston Cour       | nty      | ess tree | es were                          | marke  | ed, S75 | E 52 |

iinks 13" B. Oak and S54W 9 links 10" W. Oak.

In 1919, a survey by G.H. Dunning, County Surveyor, no object or witnesses are listed.

In 1973, an Act 132 Certified Survey by Karol R. Piotrowski, #9685, set 1/2" iron midway and online, lists two witnesses, one of which was recovered.

In 1973, an Act 74 form filed by Karol R. Piotrowski, #9685, lists same information as Act 132.

In 1993, an unrecorded survey by Charles Garlock, #14762, shows corner on sketch, no object or witnesses are listed.

In 1994, an unrecorded survey by Charles Garlock, #14762, calls for 1/2" iron rod and lists four witnesses, three of which were recovered.

## Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Common 1/4 Corner, Sections 22 & 23, T4N-R4E, Cohoctah Township, Livingston County <u>1-8</u>

Found no evidence of original government corner. Found  $\frac{1}{2}$ " iron rod on South end of tree line running North, 13'  $\pm$  West of West line of corn field to the East and 400'  $\pm$  North of tree line running East. Verified the position of the found rod with witnesses and measurements from 1973 to the present. Found no conflicting evidence in the vicinity of this position. We recommend that the found 1/2" iron rod be accepted as the best available evidence of the position of the original government corner and be replaced with a standard Livingston County monument with brass cap and carsonite post.

### Measurements:

1823 40 ch (2640') 1973 2659.13' (40.29 ch) 2000 2659.19' (40.29 ch)

1823 40 ch (2640') 1973 2659.10' (40.29 ch) 1994 2659.10' (40.29 ch)

# Description of monument for corner and accessories established to perpetuate locating the position of the

| comer.     |          |            |   |
|------------|----------|------------|---|
| <u>l-8</u> | Commo    | n 1/4 Cor  | ner, Sections 22 & 23, T4N-R4E, Cohoctah Township, Livingston County  |
|            | Set star | ndard Livi | ngston County monument with brass cap stamped "I-8 39096".  |
|            | N05W     | 47.06      | Set nail with Livingston County Survey Witness Tag in West face of a 14" Choke Cherry   |
|            | S05W     | 56.18      | North face of 4" Gas line marker  |
|            | S45W     | 165.45     | Set nail with Livingston County Survey Witness Tag in North face of South pole of E-W mark Found nail with "Hughes #19834" tag in West face of 6" Ash |
|            | N10W     | 28.55      | Found nail with "Hughes #19834" tag in West face of 6" Ash  |
|            | S75W     | 61.30      | Set nail with Livingston County Survey Witness Tag in South face of 10" Cherry  |

0.70 North Set Carsonite Marker Post

alle Signed by Surveyor's Michigan License No. 39096

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY

PEER GROUP ON 6-21-2000 CO. REP.

own the ppi RAUSER Rofescional SUBVEYOR