

# SURVEY & REMONUMENTATION

FEB 26 2001

FILED

SECTION

## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

2000 OCT 30 A 9:21

For corners in

NANCY HAVILAND  
REGISTER OF DEEDS  
LIVINGSTON COUNTY, MI.  
48843

Livingston  
(County)

Located In:  
Cohoctah Twp.

Corner Code

1. Public Land Survey

T 4N R 4E K-6

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

4. Lot No. Recorded Plat

5. Private Claims

LSC #1333m  
Register of Deeds Stamp & File Number

I, John H. Rauser, P.S., in a field survey on July 17, 2000, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5				4			3		2		1
3													
4	7	8				9			10		11		12
5													
6	18	17				16			15		14		13
7													
8	19	20				21			22		23		24
9													
10	30	29				28			27		26		25
11													
12	31	32				33			34		35		36
13													

### A. Description of original monument and accessories and/or subsequent restoration:

K-6 Common 1/4 Corner, Sections 13 & 14, T4N-R4E, Cohoctah Township, Livingston County  
1823 Wood post placed by Sylvester Sibley, Deputy Surveyor, two witness trees were marked at this time, S67E 67 links 12" B. Oak and N59W 39 links 10" B. Oak.  
In 1875, survey by Miles W. Bullock, County Surveyor, post at corner, no witnesses listed.  
In 1971, Act 132 Certified Surveys and an Act 74 forms, by Charles Garlock, #14762, found 1/2" iron rod. Listed three witnesses, two of which were recovered.  
In 1972, an Act 132 Certified Survey by Oscar Boss, #13574, calls for found 1/2" iron. Listed same three witnesses as Garlock.  
In 1982, a survey by Glenn Richard, #13040, no description of object given. Listed five witnesses, two of which were recovered.  
In 1986, a survey by Charles Garlock, #14762, shows corner on sketch. No description of object or witnesses given.  
In 1990, an Act 132 Certified Survey by Gary Boss, #17022, calls for found iron. Listed four witnesses, two of which were recovered.

### B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-6 Common 1/4 Corner, Sections 13 & 14, T4N-R4E, Cohoctah Township, Livingston County  
Found no evidence of original government corner. Found 1/2" iron 0.8" ± deep, 4" ± West of centerline of road, and online with fence to East and West. Verified the position of the found iron with witnesses and measurements from 1875 to present. Found no conflicting evidence in the vicinity of this position. We recommend that the found iron be accepted as the best available evidence of the position of the original government corner and be replaced with a standard Livingston County breakaway monument and brass cap. Corner may be suitable for GPS with some preplanning.


Measurements:

To K-7	To J-6	To L-6	To K-5
1823 40 ch (2640')	2000 2593.71' (39.30 ch)	1875 40.17 ch (2651.22')	1823 40 ch (2640')
1875 40.25 ch (2656.50')		1971 2653.40' (40.20 ch)	1875 40.25 ch (2656.50')
1972 2654.04' (40.21 ch)			1986 2651.86' (40.18 ch)
2000 2653.70' (40.21 ch)			2000 2651.89' (40.18 ch)

### C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-6 Common 1/4 Corner, Sections 13 & 14, T4N-R4E, Cohoctah Township, Livingston County  
Set standard Livingston County breakaway monument with brass cap stamped "K-6 39096"  
West 51.58' Found nail with Boss tag in South face of Power Pole (R=51.61')  
N89E 31.55' Found spike with Boss tag in North face of 10" Walnut (R=31.54')  
N20E 120.57' Found nail & tag in Southeast face of twin 12" Cherry  
N60E 37.30' Set spike with Livingston County Survey Witness tag in Southeast face of 28" Walnut  
N40W 22.70' Set PK nail with Livingston County Survey Witness tag in Northeast corner of wood fence post

Signed by John H. Rauser  
Surveyor's Michigan License No. 39096



FORM APPROVED BY MICHIGAN STATE BOARD OF SURVEYORS, MAY 14, 1975  
REVISED JAN., 1983  
ADAPTED FOR WORD PROCESSING MARCH, 1995

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY

INTER GROUP ON 6-21-2002, CO. REP JED