LAND CORNER RECORDATION CERTIFICATE

JUL 14 9 45 AH '95

For corners in		Filing Requirement of Act 74, Mich. P.A. 1970		TANGS DATILARD
	Livingston (County)	Located In:	Corner Code =##	register of Deeds Livingston county, Mi 48843
1.	Public Land Survey	T 4NR 5E T R T R T R	K=6	
۷.	Property Controlling in Section	S T R S T R		L.S.C.#419m
З.	· · · · · ·	S T R S T R		Register of Deeds Stamp & File Number
		Recorded Plat		A B C D E F G H I J K
l do in cur Ma abo Coo ext	Edward Anderson hereby certify that under req lines 1 and 2 above were in rent manual of survey instru nagement or by a decree of a ove were in conformance wit unt of Law; established, r oressed below: OTE: Not more than 4 co on this certificate.	in a field survey onJune quirements of P.A. 74, Michigan P.A. in conformance with regulations an actions of the United States Depart a Court of Law and/or that the corne th the rules of the Michigan Board of e-established, monumented, remorners, all in the same town an amonument and accessories and	of 1970, the corner points mention of 1970, the corner points mention of rules therefore as required in the interior, Bureau of Lar points mentioned in lines 3, 4 are fland Surveyors or by a Decree nonumented, recovered, found and range, may be recorded	ned the and 7 and 5 8 19 20 21 22 23 of a
	G.L.O. notes da	ted: May 11, 1823 es: W. Oak 20" S 71°	,	

Additional historical data on back

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

W. Oak 10" S84 1/2° W. 21 Lks

Found 1/2" rerod. Fit witnesses by Benton

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner.

K-6 W 1/4 COR. SEC. 13, T4N-R5E

Set 1 1/4" x 36" breakaway iron pipe with brass cap (Liv. Co. Mon. Cor.) in centerline of Green Road

N18°E 99.66' Spike W/S 14" Oak

N86°E 41.53' Spike N/S 8" Elm

N56°W 45.14' Spike N/S 18" Hickory

N23°E 57.36' Spike E/S 16" Hickory


Signed by EDWARD E ANDERSON SURVEYOR - 11495 TO ENGINEER NO. 11495 TO ENGINEER 11495

Date <u>July 5, 1995</u>

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28.

P.A. 345 1990, APPROVED BY LIVINGSTON COUNTHISED JAN.

PEER GEOLIP ON 4-19-95 CO SEP JED



EDWARD E. ANDERSON, P.S., P.E. RICHARD F. FRANK, P.S. BRIAN R. SHALTZ, C.S.T.

on Charles Mark Mark Mark 1967

Members of:
Michigan Society of Professional Surveyors
American Congress on Surveying and Mapping
American Society of Civil Engineers

401 S. Leroy St. Fenton, Michigan 48430-2164 (313) 629-8974 FAX (313) 629-9069

SUMMARY

April 4, 1995

K-6 WEST 1/4 CORNER OF SECTION 13, T4N-R5E, DEERFIELD TOWNSHIP LIVINGSTON COUNTY, MICHIGAN

Found 1/2" rerod in the centerline of Green Road (gravel)

Checked and measured to witnesses we found. Found 2 of 3 of Benton witnesses, and they checked, page 10 this dossier.

Distance from the West 1/4 corner to the N.W. corner of said Section 13 is 2662.01° as measured in the field by E.E. Anderson on 4/3/95, page 6 this dossier.

Distance from the West 1/4 corner to the S.W. corner of said Section 13 is 2669.94' on Benton Survey, page 9 this dossier.

Made a clean sweep of the immediate area and found no additional corners or irons.

Gravel road running north and south, flat in both directions.

Terrain is open to the east and wooded to the west. Old fence and tree line running east and west.

Area is not good for G.P.S.

Came to the conclusion that the 1/2" rerod we found is the correct West 1/4 corner of said Section 13.

Edwand E. Anderson P.S.#11495