

# SURVEY & REMONUMENTATION

FEB 26 2001

LAND CORNER RECORDATION CERTIFICATE

FILED

SECTION

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

2000 OCT 30 A 9:20

NANCY HAVILAND  
REGISTER OF DEEDS  
LIVINGSTON COUNTY, MI.  
48843

Livingston Located In: Corner Code #  
(County)

1. Public Land Survey T 4N R 5E E-11  
2. Property Controlling S T R  
in Section S T R  
3. Miscellaneous S T R  
Property in Sec. S T R

LSC #1319m

Register of Deeds Stamp & File Number

4. Lot No. Recorded Plat  
5. Private Claims

I, John H. Rauser, P.S., in a field survey on July 2000  
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned  
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the  
current manual of survey instructions of the United States Department of the Interior, Bureau of Land  
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5  
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a  
Court of Law; established, re-established, monumented, re-monumented, recovered, found as  
expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this  
certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	N
1													
2	6	5							3	2			1
3													
4	7	8							10	11			12
5													
6	18	17							15	14			13
7													
8	19	20							22	23			24
9													
10	30	29							27	26			25
11													
12	31	32							34	35			36
13													

A. Description of original monument and accessories and/or subsequent  
restoration:

E-11 Section corner common to Sections 28, 29, 32, & 33, T4N-R5E, Deerfield Township, Livingston County, Michigan.  
1823 Wood post placed by Sylvester Sibley, D.S.: S32E 43 lks 24" W. Oak  
N32W 49 lks 20" Swamp White Oak

(Continued on Back.)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E-11 Section corner common to Sections 28, 29, 32, & 33, T4N-R5E, Deerfield Township, Livingston County, Michigan.  
Found no evidence of original government corner. Found 1/2" rerod in monument box 1.5' South of the intersection of  
Faussett and Latson Roads. Found rerod was verified with recovered record witnesses and checked distances to adjacent  
government corners.

Measurements:

To E-10	To F-11	To E-12	To D-11
1823 40ch (2640')	1823 39.91ch (2634.06')	1823 40.00ch (2640')	1973 2631.85' (39.88ch)
1876 40.39ch (2665.74')	1969 2643.28' (40.05ch)	1876 40.39ch (2665.74')	1992 2632.31' (39.88ch)
1969 2658.40' (40.28ch)	1987 2643.00' (40.05ch)	1969 2646.07' (40.09ch)	1998 2632.27' (39.88ch)
1972 2658.40' (40.28ch)	1990 2643.31' (40.05ch)	1978 2646.04' (40.09ch)	
1973 2658.40' (40.28ch)	1994 2643.21' (40.05ch)	2000 2645.92' (40.09ch)	
1987 2658.78' (40.28ch)	1997 2643.12' (40.05ch)		
2000 2658.63' (40.28ch)	2000 2643.05' (40.05ch)		

Found no conflicting evidence in the vicinity of this position. We recommend that the found 1/2" rerod be accepted as the  
best available evidence of the original government corner and be replaced with a standard Livingston County monument  
and brass cap.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-11 Section corner common to Sections 28, 29, 32, & 33, T4N-R5E, Deerfield Township, Livingston County, Michigan.  
Set standard Livingston County monument and brass cap stamped "E-11 39096".  
N50W 177.25' Found nail/tag in South face of power pole (R=177.30')  
S80W 150.20' Found nail/tag in South face of power pole (R=150.23')  
S30E 59.60' West leg of stop sign post (R=59.55')  
N80E 104.80' Found nail/tag in South face (dead) Birch (R=104.82')  
N45E 44.57' Found 1/2" rod with Cornerstone cap #21585 (R=44.57')  
N45W 44.90' Found 1/2" rod with Cornerstone cap #21585 (R=44.89')  
S45W 45.36' Found 1/2" rod with Cornerstone cap #21585 (R=45.36')  
S45E 43.10' Found 1/2" rod with Cornerstone cap #21585 (R=43.10')



Signed by John H. Rauser  
Surveyor's Michigan License No. 39096

Date

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 7, 1974  
REVISED MAY 14, 1978  
REVISED JAN. 1983  
ADAPTED FOR WORD PROCESSING MARCH, 1993

PA. 345 1980, APPROVED BY LIVINGSTON COUNTY  
PEER GROUP ON 5-17-00 CO. REP JED