

SURVEY & REMONUMENTATION

FEB 26 2001

FILED

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

2000 OCT 30 A 9:20

SECTION

For corners in

HARCY HAVILAND
REGISTER OF DEEDS
LIVINGSTON COUNTY, MI.
48843

Livingston Located in: Corner Code #

(County)

1. Public Land Survey T 4N R 5E F 11
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

LSC #1322 m

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, John H. Rauser, P.S., in a field survey on July 2000 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

F-11 1/4 corner common to Sections 28 & 33, T4N-R5E, Deerfield Township, Livingston County, Michigan.
1823 Wood post placed by Sylvester Sibley, D.S.: N39E 6 lks 8" Elm
S73W 53 lks 10" White Oak

Continued on Back

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

F-11 1/4 corner common to Sections 28 & 33, T4N-R5E, Deerfield Township, Livingston County, Michigan.
Found no evidence of original government corner. Found "T" iron 2.95 feet South of physical centerline of Faussett Road in line with a fence line and pine tree row to the North. No occupation to the South. Verified the position of the found "T" with witnesses and measurement from 1969 to present.

Measurements:

To E-11	To G-11	To F-10
1823 39.91ch (2634.06')	1823 39.91ch (2634.06')	1998 2664.76' (40.38ch)
1969 2643.28' (40.05ch)	1969 2643.28' (40.05ch)	
1987 2643.00' (40.05ch)	1973 2643.51' (40.05ch)	
1990 2643.31' (40.05ch)	1994 2643.21' (40.05ch)	
1994 2643.21' (40.05ch)	1997 2643.35' (40.05ch)	
1997 2643.12' (40.05ch)	1998 2643.31' (40.05ch)	
2000 2643.05' (40.05ch)	2000 2643.39' (40.05ch)	

Found no conflicting evidence in the vicinity of this position. We recommend that the found "T" iron be accepted as the best available evidence of the position of the original government corner and be replaced with a Standard Livingston County monument, brass cap and monument box.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F-11 1/4 corner common to Sections 28 & 33, T4N-R5E, Deerfield Township, Livingston County, Michigan.

Set Standard Livingston County monument with brass cap stamped "F-11 39096" in monument box


North 30.38' Found Boss N&T East side of Railroad tie fence post (R=30.39')

N80E 138.02' Found Boss N&T South side of 12" Hickory (R=138.03')

S80W 182.47' Found Boss N&T North side of 30" Poplar (R=182.46')

N80W 204.76' Found Boss N&T South side of 30" Maple (R=204.77')

North 2.95' Physical centerline of Faussett Road



Signed by John H. Rauser
Surveyor's Michigan License No. 39096

Date

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 2000

REVISED MAY 14, 1976

REVISED JAN., 1983

ADAPTED FOR WORD PROCESSING MARCH, 1993

P.A. 345 1980, APPROVED BY LIVINGSTON COUNTY

PEER GROUP ON 5-17-2000, CO. REP JED