

SURVEY & REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

FILED

For corners in

Livingston Located In: Corner Code #
(County)

1. Public Land Survey T 4N R 5E H 9
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

4. Lot No. , Recorded Plat
5. Private Claims

I, John H. Rauser, P.S., in a field survey on July 2000 do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

H-9 1/4 corner common to Sections 22 & 27, T4N-R5E, Deerfield Township, Livingston County, Michigan.

1823 Wood post placed by Sylvester Sibley, D.S.: S13 1/4E 33 lks 30" W. Oak
N02E 67 lks 16" W. Oak
1875 Wm. Bullock, C.S. fnd post from previous survey. No witnesses listed.
1997 Unrecorded survey by J. Smith; no object or witnesses given.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

H-9 1/4 corner common to Sections 22 & 27, T4N-R5E, Deerfield Township, Livingston County, Michigan.

Found no evidence of original government corner. Found 3/4" rod two feet South of centerline of Dean Road with a tree line occupation to the North and South. Found no record witnesses or recent measurements to compare. The position agrees with existing occupation North and South. Found no conflicting evidence in the vicinity of this position. We recommend that the found 3/4" rod be accepted as the best available evidence of the position of the original government corner and be replaced with a standard Livingston County breakaway monument and brass cap.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:


H-9 1/4 corner common to Sections 22 & 27, T4N-R5E, Deerfield Township, Livingston County, Michigan.

Set standard Livingston County breakaway monument and brass cap stamped "H-9 39096".
S70W 72.61' Found nail with Hughes tag #19834 in North face of 24" Box Elder (R=72.61')
S40E 41.55' Found nail with Hughes tag #19834 in NE face of 15" Walnut (R=41.55')
S15E 74.54' NE corner of concrete block porch @ house #5254
N65W 55.10' Set nail with Livingston County Remon tag in South face of 8" triple Box Elder

Signed by John H. Rauser
Surveyor's Michigan License No. 39096

Date

FORM APPROVED BY MICHIGAN STATE BOARD OF



P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY
PEER GROUP ON 5-17-2000 CO. REP

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

REVISED JAN. 1991
ADAPTED FOR WORD PROCESSING MARCH, 1991