# SURVEY & REMONUMENTATION

### FEB 26 2001

#### SECTION

## LAND CORNER RECORDATION CERTIFICATE

For corners in Livingston		Filing Requirement of Act 74, Mich. P.A. 1970 2000 NOV 15 A 9: 28				
		Located In:	Corner Code ##	HANCY HAVILAND		
	(County)			HANCY HAVILAND REGISTER OF DEEDS		
1.	Public Land Survey	TR6E	1-5	LIVINGSTON COUNTY, MI. 48843		
		T R T R				
		T R				
2.	Property Controlling	S T R		LSC #1354 m		
	in Section	S T R				
3.	Miscellaneous	S T R		Register of Deeds Stamp & File Number		
	Property in Sec.	S T R	·			
4.	Lot No	, Recorded Plat		ABCDEFGHIJK		
5.	Private Claims		·	2 6 5 4 4 3 2 2		
				3		
	Ed Anderson	in a field survey on	<b>10 - 18</b> 19	2000 5		

In a field survey of \_\_\_\_\_\_, in a field survey of \_\_\_\_\_\_, in a field survey of \_\_\_\_\_\_, is \_\_\_\_\_, is \_\_\_\_\_, is \_\_\_\_\_, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior. Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

.

FILED

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

#### I-5 Found 1/2" Rod in Concrete Monument

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: I-5 Southwest corner Section 11, T4N-R6E

Set Brass	Cap (Liv. Co	o. Mon. Cor.) on Rod in Concret	te Monument	
S 35° E,	33.34	Set Nail and Liv. Co. Remon T	ag in Southwest face 3	2" Oak
N 80° E,	21.72	Set Nail and Liv. Co. Remon T	ag in South face 14" O	ak
North,	32,43'	Set Nail and Liv. Co. Remon T	ag in East face 20" Che	эгту
S 78° W,	4.90'	Set Nail and Liv. Co. Remon T	ag in northwest face 12	2" Óak
Signed by	Prod 15	EDWARD E ANDERSON SURVEYOR ENGINEER NO 149 C	Date	3 /19 /00
BA 345 1995	ABABANA	BY LIVINGSTON COUNTY	70	REVISED MAY 14, 1975
				REVISED JAN., 1983
PEER GROUP O	N <u>6.21</u>	00 CO. REP JED		