

SURVEY &  
REMONUMENTATION

FEB 26 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Livingston

(County)

Located In:

Corner Code 1-6

1. Public Land Survey

T 4N R 6E

1-6

T \_\_\_\_\_ R \_\_\_\_\_

T \_\_\_\_\_ R \_\_\_\_\_

T \_\_\_\_\_ R \_\_\_\_\_

2. Property Controlling  
in Section

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

3. Miscellaneous

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

Property in Sec.

S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_

5. Private Claims \_\_\_\_\_

2000 NOV 15 A 9:29

NANCY HAVILAND  
REGISTER OF DEEDS  
LIVINGSTON COUNTY, MI.  
48843

LSC #1355m

Register of Deeds Stamp & File Number

I, Ed Anderson, in a field survey on 10-18, 19 2000

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

**I-6 Found 'T' Iron**

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

**I-6 West 1/4 corner Section 14, T4N-R6E**


**Set 1 1/4" x 36" Iron Pipe w/Brass Cap (Liv. Co. Mon. Cor.)**

**N 15° W, 69.01' Set Nail and Liv. Co. Remon Tag in East face 14" Cottonwood**

**N 30° E, 62.28' Set Nail and Liv. Co. Remon Tag in West face 16" Cottonwood**

**S 10° W, 42.13' Set Nail and Liv. Co. Remon Tag in West face 14" Boxelder**

**S 60° W, 45.00' Set Nail and Liv. Co. Remon Tag in North face 16" Cottonwood**



P.A. 345 1990, APPROVED BY LIVINGSTON COUNTY

PEER GROUP ON 9-6-00 CO. REP SED

Signed by

Date

Surveyor's Michigan License No.